

Valves

High quality polypropylene valves adding to the range and versatility of PLASSON fittings

		Order Number	Size (mm)	
Quick Coupling Valve (10 Bar Rating)		2711	20 (¾")	<ul style="list-style-type: none"> instant on/off water supply valve compatible with GREENLINE, REDLINE™ and ALKATHENE™ pipes ideal for wash down areas and filling spray tanks
		2712	25 (1")	
Valve (10 Bar Rating)		2731	20 (¾")	<ul style="list-style-type: none"> economical BSP female threaded valve small size and rugged polypropylene body make it ideal for use around the farm
		2732	25 (1")	
Riser Key (10 Bar Rating)		2713 (Used with 2712)		<ul style="list-style-type: none"> bayonet type fitting used on end of hose to turn on PLASSON quick coupling valves
Compression Stopcock (16 Bar Rating)		2741.20	20	<ul style="list-style-type: none"> direct connection to GREENLINE, REDLINE™, RURAL BLACK and 20mm and 25mm ALKATHENE™ pipe no more leaking threaded joints cost effective – do away with threaded adapters, to connect valve to the pipe
		2741.25	25	
		2741.32	32	
Angle Seat Valve (8 Bar Rating)		2735.32	32 (1¼")	<ul style="list-style-type: none"> economical BSP male threaded valve rugged polypropylene construction to take the knocks full-bore flow performance when the valve is open
		2735.40	40 (1½")	
		2735.50	50 (2")	
Check Valve Insert (16 Bar Rating)		2720.25	25	<ul style="list-style-type: none"> check valve designed to be inserted into 25mm PLASSON fittings compatible with REDLINE™, RURAL BLACK, BLACKLINE PN16 and 20mm ALKATHENE™ pipes used for backflow protection
Valve Box		193*	155 x 200 x 200 high	<ul style="list-style-type: none"> house and protect valves and meters tough polyethylene construction snap on lid for easy access colour coded lids for asset identification <p>Notes: *Valve box only - no lid **Green lid *** lue lid</p>
		193LIDGR**	155 x 200	
		193LIDBL***	155 x 200	


Technical Specifications

Fittings

- Body - polypropylene - food grade polymer
- Backing nut - polypropylene - food grade polymer
- Split ring - acetyl
- 'O' ring - nitrile rubber (70 Shore A.NBR)

Saddles

- Reinforcing ring on BSP threaded outlets - stainless steel
- Nuts - stainless steel
- Bolts - stainless steel
- Threads - B.S.P. standard



Maximum operating pressure at 20°C

PLASSON 16 Bar