

PVC Drain Waste and Vent Fittings - Bends

Solvent Cement Joint - Non Pressure Applications Only

Novadrain is a range of high quality PVC-U Drain, Waste & Vent (DWV) pipes and fittings from Iplex Pipelines. They are suitable for above ground waste and vent applications, below ground domestic house drains, urban gravity sewer mains and Industrial gravity discharge lines.

Novadrain is certified to comply with the requirements of Best Environment Practice - PVC.

Novadrain pipes and associated PVC-U fittings are independently certified in accordance with the test requirements of AS/NZS 1260 - Standardsmark Licence No SMK20184 and SMK20185.

Product Summary

Iplex offers a complete range of bends for DWV pipe installations. Bag Quantities shown are the minimum order quantity for 32mm, 40mm & 50mm DWV fittings. Product and ordering information can be found below. For more information please contact Iplex Pipelines.

		Order Code	Size mm	Ctn / Bag Qty
Plain Bends		101.32.15	32 x 15°	200 / 10
		101.32.45	32 x 45°	160 / 5
		101.32.88	32 x 88°	120 / 5
		101.40.15	40 x 15°	60 / 5 4
		101.40.45	40 x 45°	100 / 10
		101.40.60	40 x 60°	200 / 5
		101.40.88	40 x 88°	80 / 10
		101.50.15	50 x 15°	35 / 5 6
		101.50.45	50 x 45°	55 / 5 5
		101.50.88	50 x 88°	40 / 10
		101.65.15	65 x 15°	140
		101.65.45	65 x 45°	120
		101.65.88	65 x 88°	70
		101.80.15	80 x 15°	70
		101.80.45	80 x 45°	70
		101.80.88	80 x 88°	40
		101.100.5	100 x 5°	42
		101.100.15	100 x 15°	35
		101.100.30	100 x 30°	35
		101.100.45	100 x 45°	32
101.100.60	100 x 60°	27		
101.100.88	100 x 88°	19		
101.150.15	150 x 88°	12		
101.150.45	150 x 45°	9		
101.150.88	150 x 88°	5		
Adjustable Bends		101.150A	150 x 0-45°	10

**Plain Bends
M & F**



Order Code	Size mm	Ctn / Bag Qty
171.40.42	40 x 42°	60/10
171.40.88	40 x 88°	80/10
171.50.42	50 x 42°	50/10
171.50.88	50 x 88°	40/10
171.65.42	65 x 42°	85
171.80.42	80 x 42°	60
171.80.88	80 x 88°	50
171.100.5	100 x 5°	45
171.100.11	100 x 11°	36
171.100.15	100 x 15°	35
171.100.22	100 x 22°	28
171.100.30	100 x 30°	34
171.100.42	100 x 42°	30
171.100.60	100 x 60°	27
171.100.88	100 x 88°	19
171.150.42	150 x 42°	9
171.150.88	150 x 88°	5

**Reducing
Bends M & F**



171.50.40.42	50 x 40 x 42°	50/5
--------------	---------------	------

**Inspection
Bends**



101.40.45W	40 x 45°	60 / 5
101.40.88W	40 x 88°	40 / 10
101.50.45W	50 x 45°	90 / 5
101.50.88W	50 x 88°	70 / 10
101.65.88W	65 x 88°	60
101.80.88W	80 x 88°	35
101.100.45W	100 x 45°	28
101.100.88W	100 x 88°	17

**Rear Access
Bends**



102.100.88	100 x 88°	15
------------	-----------	----

**Access
Bends**



103.100.45	100 x 45°	8
103.100.88	100 x 88°	8