

PRODUCT CATALOGUE







CONTENTS

| SECTION 1 - POLYVINYL CHLORIDE (PVC) PRESSURE SYSTEMS | | Page |
|--|--|------|
| Iplex Apollo® PVC-O Pipe | DN100 - DN300 Series 1 Metric PVC-O Pressure Pipe | 10 |
| Iplex Apollo® Blue PVC-O Pipe | DN100 - DN250 Series 2 Imperial PVC-O Pressure Pipe | 10 |
| Iplex Novakey® PVC-U Pipe | DN15 - DN575 Series 1 Metric PVC-U Pressure Pipe | 11 |
| Iplex White Rhino® PVC-M Pipe | DN100 - DN575 Series 1 Metric PVC-M Pressure Pipe | 12 |
| Iplex Blue Rhino® PVC-M Pipe | DN100 - DN150 Series 2 Imperial PVC-M Pressure Pipe | 13 |
| Iplex Novakey® PVC-U Fittings | Iplex Novakey® Series 1 Metric PVC-U Pressure Fittings | 14 |

| SECTION 2 - POLYETHYLENE (PE) PRESSURE SYSTEMS | | Page |
|--|--|------|
| Iplex Poliplex® PE100 Pipe and Mobile Extrusion | DN75 - DN710 PE100 Metric Pressure Pipe, (Pressure Water Applications) | 20 |
| Iplex Poliplex® PE100 Pipe | DN40 - DN710 PE100 Metric Pressure Pipe (Pressure Sewer & Wastewater Applications) | 21 |
| Iplex Blueline® PE80 Pipe | DN20 - DN63 PE80 Metric Pressure Pipe (CX Blue Jacket) | 22 |

| SECTION 3 - ROADING & STORMWATER SYSTEMS | | Page |
|---|--|------|
| Iplex Nexus® Hi-Way Pipe | DN110, DN160 & DN200 PE Heavy Duty Slotted Subsoil Drainage Pipe | 25 |
| Iplex Nexus® Hi-Way Pipe with Filter Sock | DN110 & DN160 PE Heavy Duty Slotted Subsoil Drainage Pipe with Filter Sock | 25 |
| Iplex Nexusflo™ Pipe with Filter Sock | DN110 & DN160 PE Slotted Subsoil Drainage Pipe with Filter Sock | 25 |
| Iplex Novaflo® with Filter Sock | DN110 & DN160 PE Slotted Subsoil Drainage Pipe with Filter Sock | 26 |
| Iplex Aquacell® | Stormwater Management System | 26 |
| Iplex Superstorm® PVC-U Pipe | DN90 – DN600 PVC-U Stormwater Pipe | 26 |
| Iplex Stormfit® PVC-U Fittings | Iplex Stormfit® PVC-U Stormwater Fittings | 27 |

CONTENTS

| SECTION 4 - PLUMBING & DWV SYSTEMS | | Page |
|---|--|------|
| Iplex Novadrain® SCJ PVC-U Pipe | DN32 - DN600 PVC-U Solvent Cement Joint Gravity DWV Pipe | 31 |
| Iplex Novadrain® RRJ PVC-U Pipe | DN32 - DN600 PVC-U Rubber Ring Joint Gravity DWV Pipe | 32 |
| Iplex Restrain® PVC-U Pipe | DN100 - DN375 Trenchless PVC-U Gravity Sewer | 33 |
| Iplex Novadrain® SCJ PVC-U Fittings | DN32 - DN150 PVC-U Solvent Cement Joint Gravity DWV Fittings | 34 |
| Iplex Novadrain® RRJ PVC-U Fittings | DN32 - DN150 PVC-U Rubber Ring Joint Gravity DWV Fittings | 41 |
| Iplex® Waste Traps, Pan Connectors and Pan Bends | DN 32 - DN100 Waste Traps, Pan Connectors and Pan Bends | 43 |
| Iplex® Pipe Support Clips | DN32 - DN150 DWV Pipe Support Clips | 44 |

| SECTION 5 - RAINWATER DOWNPIPE SYSTEMS | | Page |
|---|---|------|
| Iplex® PVC-U Downpipe, Bends, Clips and Fittings | 65mm and 80mm PVC-U Downpipe, Bends, Clips and Fittings | 47 |

| SECTION 6 - RURAL SYSTEMS | | Page |
|--------------------------------------|--|------|
| Iplex Alkathene™ LDPE Pipe | 15mm - 50mm LDPE Stock Water Pressure Pipe | 49 |
| Iplex® Irripod LDPE Pipe | 45mm LDPE Pasture Irrigation Pressure Pipe | 49 |
| Iplex® Effluent PVC-U Pipe | 80mm & 100mm Farm Dairy Effluent PVC-U Pressure Pipe | 50 |
| Iplex® Effluent PE100 Pipe | 63mm - 110mm Farm Dairy Effluent PE Pressure Pipe | 50 |
| Iplex Novatube™ LDPE Pipe | 13mm - 25mm LDPE Horticultural Lateral Tube | 50 |
| Iplex Greenline® PE100 Pipe | 20mm - 63mm PE Stock Water Pressure Pipe | 51 |
| Iplex Farmlin™ PE100 Pipe | 40mm - 63mm PE Stock Water Pressure Pipe | 51 |
| Iplex Redline® PE100 Pipe | 20mm - 63mm PE Stock Water Pressure Pipe | 51 |
| Iplex Rural Black™ PE100 Pipe | 32mm - 110mm PE Riser and Stock Water Pressure Pipe | 52 |
| Iplex Blackline™ PE100 Pipe | 25mm - 110mm PE Stock Water Pressure Pipe | 52 |

CONTENTS

| SECTION 6 - RURAL SYSTEMS | | Page |
|---|--|------|
| Iplex Blackline™ HP PE100 Pipe | 63mm - 110mm PE Stock Water Pressure Pipe | 53 |
| Iplex Blackline™ HP Ductile Iron Pressure Fittings | 63mm - 110mm Ductile Iron Pressure Fittings | 53 |
| Iplex Nexusflo™ HDPE Pipe | 110mm - 200mm Twin Wall, Smooth Bore, Slotted HDPE Land Drainage Pipe | 54 |
| Iplex Nexuscoil™ HDPE Pipe | 110mm - 200mm Twin Wall, Smooth Bore, Unslotted HDPE Duct Pipe | 54 |
| Iplex Novaflo® HDPE Pipe | 65mm - 160mm Single Wall, Corrugated Bore, Slotted HDPE Land Drainage Pipe | 54 |
| Iplex Novacoil® HDPE Duct | 65mm - 160mm Single Wall, Corrugated Bore, Unslotted HDPE Duct Pipe | 55 |
| Iplex Nexusflo™ and Novaflo® Fittings | 65mm - 250mm Couplers & Fittings | 55 |
| Iplex Nexus® Culvert PE Pipe | 110mm - 500mm Twin Wall, Smooth Bore, HDPE Culvert Pipe | 56 |
| Iplex Farmtuff® Culvert PVC-U Pipe | 110mm - 500mm PVC-U Culvert Pipe | 56 |

| SECTION 7 - ENERGY & COMMUNICATIONS SYSTEMS | | Page |
|--|--|------|
| Iplex Volta® PVC-U Rigid Electrical Conduit | 20mm - 50mm (Nominal OD) Above and Below Ground Rigid Electrical Conduit | 59 |
| Iplex Volta® PVC-U Rigid Electrical Duct | 80mm - 200mm (Nominal ID) Below Ground Rigid Electrical Duct | 59 |
| Iplex® 2700 Series PVC-U Rigid Electrical Duct | 32mm - 65mm (Nominal ID) Below Ground Rigid Electrical Duct | 60 |
| Iplex® PVC-U Electrical Bends | 50mm - 100mm (Nominal ID) PVC-U Electrical Bends | 60 |
| Iplex® PE Flexible Electrical Duct - Coils | DN32 - DN160 (Nominal OD) Below Ground Flexible Electrical Duct | 61 |
| Iplex® PE Flexible Electrical Duct - Straight Lengths | DN110 - DN160 (Nominal OD) Below Ground Flexible Electrical Duct | 62 |
| Iplex® PVC-U Rigid Communications Duct | Iplex®, Chorus & Non-Chorus Branded, Coiled PVC-U Communications Duct | 63 |
| Iplex® PE Flexible Communications Duct | Iplex®, Chorus & Non-Chorus Branded, Coiled PE Communications Duct | 64 |
| Iplex® PVC-U Communications Bends and Fittings | PVC-U Bends & Fittings for Communications Duct | 67 |
| Iplex Poligas® Metric PE Gas Pipe | DN25 - DN110 (Nominal OD) Series 1 Metric Dimension, Poligas® Gas Pipe | 68 |
| Iplex Poligas® Imperial PE Gas Pipe | 10mm - 100mm (Nominal ID) Series 3 Imperial Dimension, Poligas® Gas Pipe | 68 |

CONTENTS

| SECTION 8 - JOINTING ACCESSORIES | | Page |
|---|---|------|
| Iplex® Novakey® PVC Solvent Cement | 125ml - 4L Pressure and Non-pressure PVC Solvent Cement | 72 |
| Iplex® Novalube™ Pipe Jointing Lubricant | 500ml - 4L Pipe Jointing Lubricant (Non-Potable Water) | 72 |
| Medlube™ Pipe Jointing Lubricant | 275g - 4kg Pipe Jointing Lubricant (Potable Water) | 73 |
| Iplex® Novakey® PVC Cleaner Primer | 250ml PVC Cleaner Primer | 73 |


| ABOUT IPLEX® | | Page |
|---|--|------|
| Iplex® Quality Management Systems | Quality Assurance | 74 |
| Iplex® Pipelines New Zealand | The Company | 75 |
| New Zealand Building Code - Durability | Durability and Unsuitable Product Applications | 77 |
| Definition of Terms Used | Definitions and Pressure Conversion Table | 79 |

PVC PRESSURE SYSTEMS

SECTION 1

PVC PRESSURE SYSTEMS

IPLEX APOLLO® PVC-O PRESSURE PIPE METRIC SERIES 1 - AS/NZS 4441

| APOLLO PN6.3* (630kPa, 91 PSI) | Order Code | Size (mm) x Length (m) | Pack Qty |
|---|-----------------|------------------------------|-------------|
|  | Z880.100PN6.3.6 | 100 x 6 | 50 |
| | Z880.150PN6.3.6 | 150 x 6 | 28 |
| | Z880.200PN6.3.6 | 200 x 6 | 15 |
| | Z880.300PN6.3.6 | 300 x 6 | 6 |

Rubber Ring Joint

Note: PN6.3 is not included in AS / NZS 4441 Appendix ZZ, but has the mechanical performance capability of AS / NZS 4441

| APOLLO PN12.5 (1250kPa, 181 PSI) | Order Code | Size (mm) x Length (m) | Pack Qty |
|--|------------------|------------------------------|-------------|
|  | Z880.100PN12.5.6 | 100 x 6 | 50 |
| | Z880.150PN12.5.6 | 150 x 6 | 28 |
| | Z880.200PN12.5.6 | 200 x 6 | 15 |
| | Z880.300PN12.5.6 | 300 x 6 | 6 |

Rubber Ring Joint

| APOLLO PN10 (1000kPa, 145 PSI) | Order Code | Size (mm) x Length (m) | Pack Qty |
|--|----------------|------------------------------|-------------|
|  | Z880.100PN10.6 | 100 x 6 | 50 |
| | Z880.150PN10.6 | 150 x 6 | 28 |
| | Z880.200PN10.6 | 200 x 6 | 15 |
| | Z880.300PN10.6 | 300 x 6 | 6 |

Rubber Ring Joint

Factory Fitted Seal Ring included with each pipe

IPLEX APOLLO® BLUE PVC-O PRESSURE PIPE IMPERIAL SERIES 2 - AS/NZS 4441

| APOLLO BLUE PN12.5 (1250kPa, 181 PSI) | Order Code | Size (mm) x Length (m) | Pack Qty |
|---|------------------|------------------------------|-------------|
|  | 1880.100PN12.5.6 | 100 x 6 | 32 |
| | 1880.150PN12.5.6 | 150 x 6 | 24 |
| | 1880.200PN12.5.6 | 200 x 6 | 15 |
| | 1880.250PN12.5.6 | 250 x 6 | 12 |

Rubber Ring Joint

| APOLLO BLUE PN16 (1600kPa, 232 PSI) | Order Code | Size (mm) x Length (m) | Pack Qty |
|--|----------------|------------------------------|-------------|
|  | 1880.100PN16.6 | 100 x 6 | 32 |
| | 1880.150PN16.6 | 150 x 6 | 24 |
| | 1880.200PN16.6 | 200 x 6 | 15 |
| | 1880.250PN16.6 | 250 x 6 | 12 |



Rubber Ring Joint



Factory Fitted Seal Ring included with each pipe



SECTION 1



PVC PRESSURE SYSTEMS

IPLEX NOVAKEY® PVC-U PRESSURE PIPE METRIC SERIES 1 - AS/NZS 1477

| NOVAKEY PN6 (CLASS B, 600kPA, 87PSI) | Order Code | Size (mm) x Length (m) | Pack / Bundle Qty | SOE | RRJ |
|--|---------------|---------------------------------|-------------------------|-----|-----|
|  Solvent Cement Joint | 800.40PN6.6 | 40 x 6 | 225/5* | yes | |
| | 800.50PN6.6 | 50 x 6 | 123 | yes | yes |
| | 800.65PN6.6 | 65 x 6 | 56 | yes | yes |
| | 800.80PN6.6 | 80 x 6 | 60 | yes | yes |
| | 800.100PN66** | 100 x 6 | 40 | yes | yes |
| | 800.125PN6.6 | 125 x 6 | 32 | | yes |
| | 800.150PN66** | 150 x 6 | 28 | | yes |
| | 800.175PN6.6 | 175 x 6 | 20 | | yes |
| | 800.200PN66** | 200 x 6 | 15 | | yes |
| | 800.225PN6.6 | 225 x 6 | 12 | | yes |
|  Rubber Ring Joint | 800.250PN6.6 | 250 x 6 | 12 | | yes |
| | 800.300PN66** | 300 x 6 | 6 | | yes |
| | 800.375PN6.6 | 375 x 6 | 6 | | yes |
| | 800.450PN6.6 | 450 x 6 | 2 | | yes |
| | 800.575PN6.6 | 575 x 6 | 2 | | yes |

| NOVAKEY PN9 (CLASS C, 900kPA, 130PSI) | Order Code | Size (mm) x Length (m) | Pack / Bundle Qty | SOE | RRJ |
|--|---------------|---------------------------------|-------------------------|-----|-----|
|  Solvent Cement Joint | 800.50PN9.6 | 50 x 6 | 123 | yes | yes |
| | 800.65PN9.6 | 65 x 6 | 56 | yes | yes |
| | 800.80PN9.6 | 80 x 6 | 60 | yes | yes |
| | 800.100PN96** | 100 x 6 | 40 | yes | yes |
|  Rubber Ring Joint | 800.150PN96** | 150 x 6 | 28 | | yes |
| | 800.200PN96** | 200 x 6 | 15 | | yes |

| NOVAKEY PN12 (CLASS D, 1200kPA, 174PSI) | Order Code | Size (mm) x Length (m) | Pack / Bundle Qty | SOE | RRJ | |
|--|---|---------------------------------|-------------------------|-----|-----|-----|
|  Solvent Cement Joint | 800.32PN12.6 | 32 x 6 | 210/10* | yes | | |
| | 800.40PN12.6 | 40 x 6 | 225/5* | yes | | |
| | 800.50PN12.6 | 50 x 6 | 123 | yes | yes | |
| | 800.65PN12.6 | 65 x 6 | 56 | yes | yes | |
| | 800.80PN12.6 | 80 x 6 | 60 | yes | yes | |
| | 800.100PN126** | 100 x 6 | 40 | | yes | |
| |  Rubber Ring Joint | 800.150PN126** | 150 x 6 | 28 | | yes |
| | | 800.200PN126** | 200 x 6 | 15 | | yes |
| | | 800.250PN126** | 250 x 6 | 12 | | yes |

| NOVAKEY PN15 (CLASS E, 1500kPA, 217PSI) | Order Code | Size (mm) x Length (m) | Pack / Bundle Qty | SOE | RRJ | |
|--|---|---------------------------------|-------------------------|-----|-----|-----|
|  Solvent Cement Joint | 800.15PN15.6 | 15 x 6 | 650/10* | yes | | |
| | 800.20PN15.6 | 20 x 6 | 500/10* | yes | | |
| | 800.25PN15.6 | 25 x 6 | 320/10* | yes | | |
| | 800.32PN15.6 | 32 x 6 | 210/10* | yes | | |
| | 800.40PN15.6 | 40 x 6 | 225/5* | yes | | |
| | 800.50PN15.6 | 50 x 6 | 123 | yes | yes | |
| |  Rubber Ring Joint | 800.65PN15.6 | 65 x 6 | 56 | yes | yes |
| | | 800.80PN15.6 | 80 x 6 | 60 | yes | yes |
| | | 800.100PN15.6 | 100 x 6 | 40 | yes | yes |
| | | 800.150PN15.6 | 150 x 6 | 28 | | yes |
| 800.200PN15.6 | 200 x 6 | 15 | | yes | | |

Seal Rings included in pipe price
 *These bundle sizes are the minimum order quantity
 ** Availability may be subject to conversion to PVC-O



SECTION 1



PVC PRESSURE SYSTEMS

IPLEX WHITE RHINO® PVC-M PRESSURE PIPE METRIC SERIES 1 - AS/NZ 4765


| WHITE RHINO PN6 (600kPa, 87PSI) | Order Code | Size (mm) x Length (m) | Pack/Bundle Qty | SOE | RRJ |
|--|---------------|------------------------|-----------------|-----|-----|
|  Solvent Cement Joint | 850.100PN66** | 100 x 6 | 40 | yes | yes |
| | 850.125PN6.6 | 125 x 6 | 32 | | yes |
| | 850.150PN66** | 150 x 6 | 28 | | yes |
|  Rubber Ring Joint | 850.175PN6.6 | 175 x 6 | 20 | | yes |
| | 850.200PN66** | 200 x 6 | 15 | | yes |
| | 850.225PN6.6 | 225 x 6 | 12 | | yes |

| WHITE RHINO PN9 (900kPa, 130PSI) | Order Code | Size (mm) x Length (m) | Pack/Bundle Qty | SOE | RRJ |
|--|---------------|------------------------|-----------------|-----|-----|
|  Solvent Cement Joint | 850.100PN96** | 100 x 6 | 40 | yes | yes |
| | 850.125PN9.6 | 125 x 6 | 32 | | yes |
| | 850.150PN96** | 150 x 6 | 28 | | yes |
| | 850.175PN9.6 | 175 x 6 | 20 | | yes |
|  Rubber Ring Joint | 850.200PN96** | 200 x 6 | 15 | | yes |
| | 850.225PN9.6 | 225 x 6 | 12 | | yes |
| | 850.250PN9.6 | 250 x 6 | 12 | | yes |
| | 850.300PN96** | 300 x 6 | 6 | | yes |
| | 850.375PN9.6 | 375 x 6 | 6 | | yes |
| | 850.450PN9.6 | 450 x 6 | 2 | | yes |
| | 850.575PN9.6 | 575 x 6 | 2 | | yes |

| WHITE RHINO PN12 (1200kPa, 174PSI) | Order Code | Size (mm) x Length (m) | Pack/Bundle Qty | SOE | RRJ |
|--|-----------------|------------------------|-----------------|-----|-----|
|  Solvent Cement Joint | 850.100PN12.6** | 100 x 6 | 40 | yes | yes |
| | 850.125PN12.6 | 125 x 6 | 32 | | yes |
| | 850.150PN12.6** | 150 x 6 | 28 | yes | yes |
| | 850.175PN12.6 | 175 x 6 | 20 | | yes |
| | 850.200PN12.6** | 200 x 6 | 15 | yes | yes |
|  Rubber Ring Joint | 850.225PN12.6 | 225 x 6 | 12 | | yes |
| | 850.250PN12.6 | 250 x 6 | 12 | | yes |
| | 850.300PN12.6** | 300 x 6 | 6 | | yes |
| | 850.375PN12.6 | 375 x 6 | 6 | | yes |
| | 850.450PN12.6 | 450 x 6 | 2 | | yes |

| WHITE RHINO PN15 (1500kPa, 217PSI) | Order Code | Size (mm) x Length (m) | Pack/Bundle Qty | SOE | RRJ |
|--|-----------------|------------------------|-----------------|-----|-----|
|  Solvent Cement Joint | 850.100PN15.6** | 100 x 6 | 40 | yes | yes |
| | 850.125PN15.6 | 125 x 6 | 32 | | yes |
| | 850.150PN15.6** | 150 x 6 | 28 | | yes |
|  Rubber Ring Joint | 850.175PN15.6 | 175 x 6 | 20 | | yes |
| | 850.200PN15.6** | 200 x 6 | 15 | | yes |
| | 850.250PN15.6** | 250 x 6 | 12 | | yes |


Seal Rings included in pipe price
** Availability may be subject to conversion to PVC-O.

| Z Joint Seal rings | Order Code | Size (mm) | Pack Qty |
|---|-----------------------------------|-----------|----------|
|  Z Joint Seal Ring for Metric Series 1 Novakey or White Rhino Pipe | Seal Rings included in pipe price | | |
| | 860.50 | 50 | 1 |
| | 860.65 | 65 | 1 |
| | 860.80 | 80 | 1 |
| | 860.125 | 125 | 1 |
| | 860.450 | 450 | 1 |


SECTION 1

PVC PRESSURE SYSTEMS

IPLEX BLUE RHINO® PVC-M PRESSURE PIPE IMPERIAL SERIES 2 - AS/NZ 4765

| BLUE RHINO PN12 (CLASS D, 1200kPA, 174PSI) | Order Code | Size (mm) x Length (m) | Pack Qty |
|---|----------------------|---------------------------------|-------------|
|  | 1850.100PN12.6 RRJ** | 100 x 6 | 32 |
| Rubber Ring Joint | 1850.150PN12.6 RRJ** | 150 x 6 | 18 |

Factory Fitted Seal Rings included in pipe price
** Availability may be subject to conversion to PVC-O

| BLUE RHINO PN16 (CLASS E, 1600kPA, 232PSI) | Order Code | Size (mm) x Length (m) | Pack Qty |
|--|----------------------|---------------------------------|-------------|
|  | 1850.100PN16.6 RRJ** | 100 x 6 | 32 |
| Rubber Ring Joint | 1850.150PN16.6 RRJ** | 150 x 6 | 18 |




Factory Fitted Seal Rings included in pipe price
** Availability may be subject to conversion to PVC-O

SECTION 1

PVC PRESSURE SYSTEMS

IPLEX NOVAKEY® PVC-U PRESSURE FITTINGS - SCJ METRIC SERIES 1 - AS / NZS 1477

(COMPATIBLE WITH IPLEX PVC-O, PVC-U & PVC-M PRESSURE PIPE METRIC SERIES 1)

| | Order Code | Size (mm) | Ctn / Bag Qty | Pressure Rating (Bar) |
|---|-------------|-----------|---------------|-----------------------|
|  Plain 90° Elbow F&F | 801.15.90 | 15 | 440/10 | 18 |
| | 801.20.90 | 20 | 250/10 | 18 |
| | 801.25.90 | 25 | 120/10 | 18 |
| | 801.32.90 | 32 | 80/10 | 18 |
| | 801.40.90 | 40 | 50/10 | 18 |
| | 801.50.90 | 50 | 25/5 | 18 |
| | 801.65.90 | 65 | 15 | 15 |
| | 801.80.90 | 80 | 9 | 15 |
| | 801.100.90 | 100 | 5 | 15 |
| | 801.125.90* | 125 | 5 | 15 |
| | 801.150.90 | 150 | 2 | 12 |
| 801.200.90* | 200 | 2 | 10 | |
|  Plain 45° Elbow F&F | 801.15.45 | 15 | 400/10 | 18 |
| | 801.20.45 | 20 | 260/10 | 18 |
| | 801.25.45 | 25 | 150 | 18 |
| | 801.32.45 | 32 | 80/10 | 18 |
| | 801.40.45 | 40 | 50/10 | 18 |
| | 801.50.45 | 50 | 25/5 | 18 |
| | 801.65.45* | 65 | 12 | 16 |
| | 801.80.45 | 80 | 12 | 15 |
| | 801.100.45 | 100 | 6 | 15 |
| | 801.125.45* | 125 | 6 | 15 |
|  Plain 90° Tee F&F | 804.15 | 15 | 300/10 | 18 |
| | 804.20 | 20 | 150/10 | 18 |
| | 804.25 | 25 | 100/5 | 18 |
| | 804.32 | 32 | 60/10 | 18 |
| | 804.40 | 40 | 30/10 | 18 |
| | 804.50 | 50 | 20/5 | 18 |
| | 804.65 | 65 | 12 | 15 |
| | 804.80 | 80 | 6 | 15 |
| | 804.100 | 100 | 4 | 15 |
| | 804.125* | 125 | 6 | 15 |
| | 804.150 | 150 | 1 | 12 |
| 804.200* | 200 | 1 | 10 | |

| | Order Code | Size (mm) | Ctn / Bag Qty | Pressure Rating (Bar) |
|--|------------|-----------|---------------|-----------------------|
|  Plain 90° Reducing Tee F&F&F | 805.20.15 | 20 x 15 | 150/10 | 18 |
| | 805.25.20 | 25 x 20 | 90/10 | 18 |
| | 805.32.25 | 32 x 25 | 60/10 | 18 |
| | 805.40.32 | 40 x 32 | 80/20 | 18 |
| | 805.50.40 | 50 x 40 | 25/5 | 18 |
| | 805.80.50 | 80 x 50 | 9 | 15 |
| | 805.100.50 | 100 x 50 | 4 | 15 |
|  Faucet Coupling F&F## | 806.15 | 15 | 500/10 | 18 |
| | 806.20 | 20 | 320/10 | 18 |
| | 806.25 | 25 | 180/10 | 18 |
| | 806.32 | 32 | 120/10 | 18 |
| | 806.40 | 40 | 80/10 | 18 |
| | 806.50 | 50 | 50/5 | 18 |
| | 806.80 | 80 | 44 | 15 |
| 806.100 | 100 | 12 | 15 | |
|  Faucet 90° Tee F&F## | 807.15 | 15 | 280/10 | 18 |
| | 807.20 | 20 | 200/10 | 18 |
| | 807.25 | 25 | 80/10 | 18 |
|  Faucet Elbow F&F## | 808.15.90 | 15 | 380/10 | 18 |
| | 808.20.90 | 20 | 200/10 | 18 |
| | 808.25.90 | 25 | 120/10 | 18 |
| | 808.32.90 | 32 | 70/10 | 18 |

*Grey fitting with parallel sockets.

Note: The Bag Quantity shown is the minimum order quantity for 15mm to 50mm pressure fittings

Moulded PVC-U Sealing threads comply with relevant parts of AS/ISO 7.1 and AS/ISO 7.2




Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex pressure fittings in this range may be subject to change without notice.





SECTION 1

PVC PRESSURE SYSTEMS

IPLEX NOVAKEY® PVC-U PRESSURE FITTINGS - SCJ METRIC SERIES 1 - AS / NZS 1477

(COMPATIBLE WITH IPLEX PVC-O, PVC-U & PVC-M PRESSURE PIPE METRIC SERIES 1)

| | Order Code | Size (mm) | Ctn / Bag Qty | Pressure Rating (Bar) |
|--|---|-----------|---------------|-----------------------|
|  Compression Coupling F&F | 809.15* | 15 | 10 | 12 |
| | 809.20* | 20 | 120 | 12 |
| | 809.25* | 25 | 10 | 12 |
| | 809.32* | 32 | 50 | 12 |
| | 809.40* | 40 | 10 | 12 |
| | 809.50* | 50 | 20 | 12 |
| | * Rubber Ring compression style joint. These fittings can be purchased individually | | | |
|  Plain Coupler F&F | 810.15 | 15 | 420/10 | 18 |
| | 810.20 | 20 | 400/10 | 18 |
| | 810.25 | 25 | 230/10 | 18 |
| | 810.32 | 32 | 140/10 | 18 |
| | 810.40 | 40 | 80/10 | 18 |
| | 810.50 | 50 | 50/5 | 18 |
| | 810.65 | 65 | 28 | 15 |
| | 810.80 | 80 | 18 | 15 |
| | 810.100 | 100 | 10 | 15 |
| | 810.150 | 150 | 2 | 12 |
|  Socket Union F&F | 811.15 | 15 | 160/10 | 18 |
| | 811.20 | 20 | 140/20 | 18 |
| | 811.25 | 25 | 80/10 | 18 |
| | 811.32 | 32 | 60/10 | 18 |
| | 811.40 | 40 | 45/5 | 18 |
| | 811.50 | 50 | 30/5 | 18 |
| | These fittings can be purchased individually. | | | |

| | Order Code | Size (mm) | Ctn / Bag Qty | Pressure Rating (Bar) |
|---|---|-----------|---------------|-----------------------|
|  Valve Socket M&F## | 813.15 | 15 | 550/10 | 18 |
| | 813.20 | 20 | 320/10 | 18 |
| | 813.25 | 25 | 200/10 | 18 |
| | 813.32 | 32 | 130/10 | 18 |
| | 813.40 | 40 | 100/10 | 18 |
| | 813.50 | 50 | 50/5 | 18 |
| | 813.65 | 65 | 40 | 12 |
| | 813.80 | 80 | 30 | 15 |
| | 813.100 | 100 | 16 | 15 |
| |  Valve Spigot M&M## | 817.15 | 15 | 650/10 |
| 817.20 | | 20 | 350/10 | 18 |
| 817.25 | | 25 | 240/10 | 18 |
| 817.32 | | 32 | 140/10 | 18 |
| 817.40 | | 40 | 110/10 | 18 |
| 817.50 | | 50 | 60/5 | 18 |
|  Threaded Bush M&F## | | 818.20.15 | 20x15 | 800/10 |
| | 818.25.20 | 25x20 | 400/10 | 18 |
|  Reducing Socket F&F | 823.20.15 | 20x15 | 380/10 | 18 |
| | 823.25.20 | 25x20 | 260/10 | 18 |
| | 823.32.25 | 32x25 | 120/10 | 18 |
| | 823.40.32 | 40x32 | 70/10 | 18 |
| | 823.50.40 | 50x40 | 60/5 | 18 |
| | 823.65.50 | 65x50 | 48 | 15 |
| | 823.80.50 | 80x50 | 30 | 15 |
| | 823.80.65 | 80x65 | 18 | 15 |
| | 823.100.80 | 100x80 | 16 | 15 |
| | 823.125.100 | 125x100 | 6 | 15 |
| 823.150.100 | 150x100 | 4 | 12 | |

Moulded PVC-U Sealing threads comply with relevant parts of AS/ISO 7.1 and AS/ISO 7.2




Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex pressure fittings in this range may be subject to change without notice.

SECTION 1

PVC PRESSURE SYSTEMS

IPLEX NOVAKEY® PVC-U PRESSURE FITTINGS - SCJ METRIC SERIES 1 - AS / NZS 1477

(COMPATIBLE WITH IPLEX PVC-O, PVC-U & PVC-M PRESSURE PIPE METRIC SERIES 1)

| | Order Code | Size (mm) | Ctn / Bag Qty | Pressure Rating (Bar) |
|--|--------------|-----------|---------------|-----------------------|
|  Reducing Bush M&F | 824.20.15 | 20x15 | 850/10 | 18 |
| | 824.25.15 | 25x15 | 750/10 | 18 |
| | 824.25.20 | 25x20 | 600/10 | 18 |
| | 824.32.25 | 32x25 | 370/10 | 18 |
| | 824.40.25 | 40x25 | 280/10 | 18 |
| | 824.40.32 | 40x32 | 280/10 | 18 |
| | 824.50.25 | 50x25 | 120/5 | 18 |
| | 824.50.40 | 50x40 | 120/5 | 18 |
| | 824.65.50 | 65x50 | 90 | 15 |
| | 824.80.50 | 80x50 | 55 | 15 |
| | 824.80.65* | 80x65 | 36 | 15 |
| | 824.100.50 | 100x50 | 30 | 15 |
| | 824.100.80 | 100x80 | 30 | 15 |
| | 824.125.100* | 125x100 | 20 | 12 |
| | 824.150.100 | 150x125 | 9 | 12 |
| 824.150.125* | 150x125 | 9 | 12 | |
|  Full Face Flange F (Use with 842 Gasket) | 825.50 | 50 | 30 | 18 |
| | 825.65 | 65 | 20 | 15 |
| | 825.80 | 80 | 12 | 15 |
| | 825.100 | 100 | 9 | 15 |
| | 825.150 | 150 | 4 | 12 |
|  Stub Flange F (Use with 827 Backing Ring & 845 Gasket) | 826.50* | 50 | 48 | 18 |
| | 826.65 | 65 | 42 | 15 |
| | 826.80 | 80 | 25 | 15 |
| | 826.100 | 100 | 14 | 15 |
| | 826.125* | 125 | 8 | 16 |
| | 826.150 | 150 | 4 | 12 |
| | 826.200* | 200 | 6 | 10 |
| | 826.300* | 300 | 3 | 10 |

NB: Holes must be drilled to suit the application. Same method can be used with some non-British standard flanges.

| | Order Code | Size (mm) | Ctn / Bag Qty | Pressure Rating (Bar) | |
|---|---|-----------|---------------|-----------------------|----|
|  Metal Backing Ring for 826 Stub Flange Drilled to AS2129 (BS10) Table E | 827.50 | 50 | 100/1 | | |
| | 827.65 | 65 | 100/10 | | |
| | 827.80 | 80 | 100/10 | | |
| | 827.100 | 100 | 100/10 | | |
| | 827.125 | 125 | 10/1 | | |
| | 827.150 | 150 | 100/10 | | |
| | 827.200 | 200 | 50/1 | | |
| | 827.300 | 300 | 10/1 | | |
| |  Plain End Cap F | 830.15 | 15 | 600/10 | 18 |
| | | 830.20 | 20 | 500/10 | 18 |
| 830.25 | | 25 | 300/10 | 18 | |
| 830.32 | | 32 | 220/10 | 18 | |
| 830.40 | | 40 | 160/10 | 18 | |
| 830.50 | | 50 | 80/5 | 18 | |
| 830.65 | | 65 | 48 | 15 | |
| 830.80 | | 80 | 36 | 15 | |
| 830.100 | | 100 | 20 | 15 | |
| 830.125 | | 125 | 14 | 15 | |
| 830.150 | 150 | 5 | 12 | | |
|  Threaded End Plug M## | 837.15 | 15 | 900/10 | 18 | |
| | 837.20 | 20 | 700/10 | 18 | |
| | 837.25 | 25 | 500/10 | 18 | |
| | 837.32 | 32 | 120/10 | 18 | |
| | 837.40 | 40 | 100/10 | 18 | |
| | 837.50 | 50 | 50/5 | 18 | |
| | 837.80 | 80 | 40 | 15 | |
| 837.100 | 100 | 12 | 15 | | |
|  Pipe Clip | 840.15 | 15 | | | |
| | 840.20 | 20 | | | |
| | 840.25 | 25 | | | |
| | 840.32 | 32 | | | |
| | 840.40 | 300 | | | |
| 840.50 | 300 | | | | |



Moulded PVC-U Sealing threads comply with relevant parts of AS/ISO 7.1 and AS/ISO 7.2
*Grey fittings with parallel sockets.

Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex pressure fittings in this range may be subject to change without notice.

SECTION 1

PVC PRESSURE SYSTEMS

IPLEX NOVAKEY® PRESSURE FLANGE GASKETS

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|--|------------|-----------|--------------|
|  <p>Neoprene Gasket for Full Face Flange 825</p> | 842.50 | 50 | 1 |
| | 842.65 | 65 | 1 |
| | 842.80 | 80 | 1 |
| | 842.100 | 100 | 1 |
| | 842.150 | 150 | 1 |
|  <p>Neoprene Gasket for Stub Flange 826</p> | 845.50 | 50 | 1 |
| | 845.65 | 65 | 1 |
| | 845.80 | 80 | 1 |
| | 845.100 | 100 | 1 |
| | 845.125 | 125 | 1 |
| | 845.150 | 150 | 1 |
| | 845.200 | 200 | 1 |
| | 845.300 | 300 | 1 |

Maximum working pressure size range:
NOVAKEY® Moulded PVC-U fittings (except as stated)

15-50mm1800kPa, PN18

65-125mm1500kPa, PN15


150mm1200kPa, PN12

200mm1000kPa, PN10

This is a general guide only. If in doubt, check the pressure rating on the fitting or contact Iplex Pipelines at <https://www.iplex.co.nz/contact/>

Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex pressure fittings in this range may be subject to change without notice.

NOTES



PE PRESSURE SYSTEMS

SECTION 2

PE PRESSURE SYSTEMS

IPLEX POLIPLEX® AND MOBILE EXTRUSION PE100 PRESSURE PIPE - AS/NZS 4130

PRESSURE WATER APPLICATIONS

| | Order Code | Size (mm)# | Colour Options# | PN Class Options# | Maximum Length Options (m)# | Drum Coil Length Options (m)# |
|--|------------|------------|-----------------|---------------------------------|-----------------------------|-------------------------------|
|  Black Pipe - 100m Lengths Manufactured on Site | 3500.75 | 75 | B, CX, MS | 4 6.3, 8, 10, 12.5, 16 | 12, 100, 200 | 1000 |
| | 3500.90 | 90 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, 20, 25 | 12, 100 | 850 |
| | 3500.110 | 110 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, | 12, 100 | 600 |
|  CX Blue Pipe - Lengths | 3500.125 | 125 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, 20 | 15, 18, 100 | 500 |
| | 3500.140 | 140 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, | 15, 18, 100 | 340 |
| | 3500.160 | 160 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16 | 18, 22, 100 | |
|  Iplex NZ Mobile Extrusion Factory | 3500.180 | 180 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16 | 18, 22 | |
| | 3500.200 | 200 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, 25 | 18, 22 | |
| | 3500.225 | 225 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, | 18, 22 | |
| | 3500.250 | 250 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, 20, | 18, 22 | |
| | 3500.280 | 280 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, | 18, 25 | |
|  Black Pipe - Coils | 3500.315 | 315 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, 20, | 18, 25 | |
| | 3500.355 | 355 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, 20 | 18, 25 | |
| | 3500.400 | 400 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, | 18, 25 | |
|  CX Blue Pipe - Coils | 3500.450 | 450 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, | 18, 25 | |
| | 3500.500 | 500 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16, 20, | 17, 18, 25 | |
|  MS Blue Stripe Pipe - Coils | 3500.560 | 560 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16 | 16, 18, 25 | |
| | 3500.630 | 630 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16 | 14, 16, 18, 25 | |
| | 3500.710 | 710 | B, CX, MS | 4, 6.3, 8, 10, 12.5, 16 | 15, 25 | |

Availability

- 3500 Series products are not necessarily held stock and may be subject to minimum production quantities, manufacturing lead times and tooling availability

Lengths

- Maximum lengths available are subject to PN Class and weight limits
- All pipe lengths are subject to PN class, maximum weight limits, and maximum length limits to transport manufacturing lead times and tooling availability

Colours

- 3500 Series pipe colour options may include black, or coloured coextruded (CX) jackets, or coloured Multi-stripes (MS), including Blue, Cream, or Purple and may be subject to minimum production quantities, manufacturing lead times and tooling availability

Drum Coils

- All Drum Coil lengths are subject to PN class, maximum weight limits and maximum length limits to transport, manufacturing lead times and tooling availability

SECTION 2

PE PRESSURE SYSTEMS

IPLEX POLIPLEX® PE100 PRESSURE PIPE - AS/NZS 4130

PRESSURE SEWER & WASTE WATER APPLICATIONS

| | Order Code | Size (mm) | Colour Options# | PN Class Options# | Maximum Length# Options (m) | Drum Coil Length # Options (m) |
|--|------------|-----------|-----------------|-------------------|-----------------------------|--------------------------------|
|  <p>CMS Cream Multi-striped Pipe</p> | 3100.40 | 40 | CX, MS | 16 | 100, 700 | |
| | 3100.50 | 50 | CX, MS | 16 | 100, 300 | |
| | 3100.63 | 63 | CX, MS | 16 | 100, 200 | |
| | 3100.75 | 75 | CX, MS | 12.5, 16 | 200 | 1000 |
| | 3100.90 | 90 | CX, MS | 12.6, 16 | 100 | 850 |
| | 3100.110 | 110 | CX, MS | 12.5, 16 | 100 | 600 |
|  <p>CX Cream Jacket Pipe</p> | 3100.125 | 125 | CX, MS | 12.5, 16 | 18, 100 | 500 |
| | 3100.140 | 140 | CX, MS | 12.5, 16 | 18, 100 | 340 |
| | 3100.160 | 160 | CX, MS | 12.5, 16 | 18, 100 | 300 |
| | 3100.180 | 180 | CX, MS | 12.5, 16 | 18 | |
| | 3100.200 | 200 | CX, MS | 12.5, 16 | 18 | |
| | 3100.225 | 225 | CX, MS | 12.5, 16 | 18 | |
| | 3100.250 | 250 | CX, MS | 12.5, 16 | 18 | |
| | 3100.280 | 280 | CX, MS | 12.5, 16 | 18 | |
| | 3100.315 | 315 | CX, MS | 12.5, 16 | 18 | |
| | 3100.355 | 355 | CX, MS | 12.5, 16 | 18 | |
|  <p>Black Pipe - Drum Coil</p> | 3100.400 | 400 | CX, MS | 12.5, 16 | 18 | |
| | 3100.450 | 450 | CX, MS | 12.5, 16 | 18 | |
| | 3100.500 | 500 | CX, MS | 12.5, 16 | 16, 17, 18 | |
| | 3100.560 | 560 | CX, MS | 12.5, 16 | 16, 18 | |
| | 3100.630 | 630 | CX, MS | 12.5, 16 | 14, 16, 18 | |
| | 3100.710 | 710 | CX, MS | 12.5, 16 | 12, 15 | |

Availability

- 3100 Series products are not necessarily held stock and may be subject to minimum production quantities, manufacturing lead times and tooling availability

Lengths

- Maximum lengths available are subject to PN Class and weight limits
- All pipe lengths are subject to PN class, maximum weight limits, and maximum length limits to transport

Colours

- 3100 Series pipe colour options may include cream coextruded (CX) jackets, or cream Multi-stripes (MS), and may be subject to minimum production quantities, manufacturing lead times and tooling availability

Drum Coils


- All Drum Coil lengths are subject to PN class, maximum weight limits and maximum length limits to transport, manufacturing lead times and tooling availability

SECTION 2


PE PRESSURE SYSTEMS

IPLEX BLUELINE® PE80 PRESSURE PIPE - AS/NZS 4130

PRESSURE WATER APPLICATIONS

|  | Order Code | Size (mm) | Coil length (m) | Order Code | Size (mm) | Coil length (m) |
|---|-------------------|-----------|-----------------|-------------------|-----------|-----------------|
| | | | | | | |
| CX Blue Jacket Pipe PN12.5 | 2500.20PN12.5.25 | 20 | 25 | 2500.40PN12.5.25 | 40 | 25 |
| | 2500.20PN12.5.50 | 20 | 50 | 2500.40PN12.5.50 | 40 | 50 |
| | 2500.20PN12.5.100 | 20 | 100 | 2500.40PN12.5.100 | 40 | 100 |
| | 2500.25PN12.5.25 | 25 | 25 | 2500.50PN12.5.25 | 50 | 25 |
| | 2500.25PN12.5.50 | 25 | 50 | 2500.50PN12.5.50 | 50 | 50 |
| | 2500.25PN12.5.100 | 25 | 100 | 2500.50PN12.5.100 | 50 | 100 |
| | 2500.32PN12.5.25 | 32 | 25 | 2500.63PN12.5.25 | 63 | 25 |
| | 2500.32PN12.5.50 | 32 | 50 | 2500.63PN12.5.50 | 63 | 50 |
| | 2500.32PN12.5.100 | 32 | 100 | 2500.63PN12.5.100 | 63 | 100 |

COMBINATION AIR VALVES

|  | Order Code | Size | Ctn/Bag | Pressure Rating (Bar) |
|---|------------|------|---------|-----------------------|
| | 2740.15 | ½" | 1 | 16 |
| | 2740.20 | ¾" | 1 | 16 |
| | 2740.25 | 1" | 1 | 16 |

POLYETHYLENE WATER METER VALVE BOXES

|  | Order Code | Size (mm) | Qty |
|---|-------------|----------------------|-----|
| Polyethylene (Water Meter) Valve Boxes Blue Lid Green Lid | 193* | 155 x 200 x 200 high | 10 |
| | 193LIDGR** | 155 x 200 | 80 |
| | 193LIDBL*** | 155 x 200 | 80 |

* Valve box only - no lid ** Green lid *** Blue lid


ROADING & STORMWATER SYSTEMS

SECTION 3

ROADING & STORMWATER SYSTEMS


IPLEX NEXUS® HI-WAY SUBSOIL DRAINAGE PIPE

ROAD DRAINAGE SYSTEM TWIN WALL SMOOTH BORE HEAVY
DUTY PE (SLOTTED)
(COMPLIES WITH NZTA SPECIFICATION TNZ F/2)

| | Order Code | Size (mm) | Length (m) | SN (KN/m ²) |
|---|---------------|-----------|------------|-------------------------|
|  <p>Black Pipe with Red Stripe Supplied with Push Fit Coupler</p> | NEXUS1105HD | 110 | 5 | 10 |
| | NEXUS11050HD | 110 | 50 | 10 |
| | NEXUS110100HD | 110 | 100 | 10 |
| | NEXUS1605HD | 160 | 5 | 10 |
| | NEXUS16045HD | 160 | 45 | 10 |
| | NEXUS2005HD | 200 | 5 | 5 |

IPLEX NEXUS® HI-WAY WITH FILTER SOCK SUBSOIL DRAINAGE PIPE

ROAD DRAINAGE SYSTEM TWIN WALL SMOOTH BORE HEAVY
DUTY PE (SLOTTED - WITH FILTER SOCK)
(COMPLIES WITH NZTA SPECIFICATION TNZ F/2)

| | Order Code | Size (mm) | Length (m) | SN (KN/m ²) |
|--|-----------------|-----------|------------|-------------------------|
|  <p>Black Pipe with Red Stripe Supplied with Pre-applied Filter Sock & Coupler</p> | NEXUS110100HDFS | 110 | 100 | 10 |
| | NEXUS16045HDFS | 160 | 45 | 10 |

IPLEX NEXUSFLO™ WITH FILTER SOCK SUBSOIL DRAINAGE PIPE

LAND DRAINAGE SYSTEM TWIN WALL SMOOTH BORE PE
(SLOTTED - WITH FILTER SOCK)

| | Order Code | Size (mm) | Length (m) | SN (KN/m ²) |
|---|----------------|-----------|------------|-------------------------|
|  <p>Black Pipe with Blue Stripe Supplied with Pre-applied Filter Sock & Coupler</p> | NEXUS110100FS* | 110 | 100 | 6 |
| | NEXUS16045FS* | 160 | 45 | 6 |

*Complies with NZTA SPECIFICATION TNZ F/5

SECTION 3

ROADING & STORMWATER SYSTEMS

IPLEX NOVAFLO® WITH FILTER SOCK SUBSOIL DRAINAGE PIPE

LAND DRAINAGE SYSTEM SINGLE WALL CORRUGATED BORE
PE (SLOTTED - WITH FILTER SOCK)

| | Order Code | Size (mm) | Length (m) | SN |
|---|---------------|-----------|------------|----|
|  <p>Black Pipe with Pre-applied Filter Sock & Coupler</p> | 400.110.30FS | 110 | 30 | 6 |
| | 400.110.100FS | 110 | 100 | 6 |
| | 400.160.45FS | 160 | 45 | 6 |


IPLEX AQUACELL® STORMWATER MANAGEMENT SYSTEM

| | Order Code | Size (mm) | Qty |
|--|---------------|------------------------------------|-----|
|  <p>Unit</p> | AQUACELL UNIT | 1000mm (L) x 500mm (W) x 400mm (H) | 10 |
|  <p>Clip</p> | AQUACELL CLIP | | 500 |

IPLEX SUPERSTORM® PVC-U STORMWATER DUCT NON PRESSURE APPLICATIONS ONLY - AS/NZS 1254

SUPERSTORM® 4000 PVC-U STORMWATER DUCT SOLVENT CEMENT JOINT & RUBBER RING JOINT - SN4

| | Order Code | Size (mm) | Ctn Qty |
|--|------------------|-----------|---------|
|  <p>Solvent Cement Joint</p> | 700SN4.90.6 SOE | 90 x 6 | 81 |
| | 700SN4.100.6 SOE | 100 x 6 | 67 |
| | 700SN4.150.6 SOE | 150 x 6 | 28 |
| | 700SN4.175.6 SOE | 175 x 6 | 20 |
| | 700SN4.225.6 SOE | 225 x 6 | 12 |

| | Order Code | Size (mm) | Ctn Qty |
|--|---------------|-----------|---------|
|  <p>Rubber Ring Joint</p> | Z700SN4.150.6 | 150 x 6 | 28 |
| | Z700SN4.175.6 | 175 x 6 | 20 |
| | Z700SN4.225.6 | 225 x 6 | 12 |
| | Z700SN4.300.6 | 300 x 6 | 6 |
| | Z700SN4.375.6 | 375 x 6 | 6 |
| | Z700SN4.475.6 | 475 x 6 | 4 |
| Z700SN4.600.6 | 600 x 6 | 2 | |

SECTION 3

ROADING & STORMWATER SYSTEMS

IPLEX STORMFIT® PVC-U STORMWATER FITTINGS - NON PRESSURE APPLICATIONS

NON PRESSURE APPLICATIONS ONLY

| | Order Code | Size (mm) | Ctn Qty |
|---|---|-----------|---------|
|  | 701.90.15 | 90 x 15° | 110 |
| | 701.90.22 | 90 x 22° | 110 |
| | 701.90.45 | 90 x 45° | 80 |
| | 701.90.90 | 90 x 90° | 60 |
| | 101.100.5 | 100 x 5° | 42 |
| | 101.100.15 | 100 x 15° | 35 |
| | 101.100.30 | 100 x 30° | 35 |
| | 101.100.45 | 100 x 45° | 32 |
| | 101.100.88 | 100 x 88° | 19 |
| | 701.150.45 | 150 x 45° | 12 |
| | 701.150.90 | 150 x 90° | 8 |
| Plain Bend F&F | | | |
|  | 771.90.45MF | 90 x 45° | 75 |
| Plain Bend M&F | | | |
|  | 103.100.45 | 100 x 45° | 8 |
| | 103.100.88 | 100 x 88° | 8 |
| Access Bend F&F | | | |
|  | 704.90.45** | 90 x 45° | 28 |
| | 704.90.90* | 90 x 88° | 40 |
| | 104.100.45*** | 100 x 45° | 12 |
| | 104.100.88** | 100 x 88° | 14 |
| | 704.150.45** | 150 x 45° | 4 |
| | 704.150.90*** | 150 x 90° | 5 |
| | Plain Junction F&F&F (SCJ) | | |
| | *Threaded on branch socket **Threaded on one main way socket ***Threaded on one main way socket and branch socket | | |

| | Order Code | Size (mm) | Ctn Qty |
|---|--------------------|-----------------|---------|
|  | 704.150.100.45 | 150 x 100 x 45° | 5 |
| Reducing Junction F&F | | | |
|  | 105.100.45LH | 100 x 45° | 7 |
| | 105.100.45RH | 100 x 45° | 7 |
| Inspection Junction F&F&F | | | |
|  | 710.90* | 90 | 140 |
| | 110.100 | 100 | 45 |
| | 110.150 | 150 | 14 |
| Straight Coupling F&F | | | |
| Straight Coupling with Threaded End F&F | * Threaded fitting | | |
|  | 711S.90 | 90 | 72 |
| Slip Repair Coupling F&F | | | |
|  | 711R.90 | 90 | 80 |
| Repair Coupling F&F | | | |


Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex stormwater fittings may be subject to change without notice.






SECTION 3

ROADING & STORMWATER SYSTEMS

IPLEX STORMFIT® PVC-U STORMWATER FITTINGS - NON PRESSURE APPLICATIONS

NON PRESSURE APPLICATIONS ONLY

| | Order Code | Size (mm) | Ctn Qty |
|--|--|-----------|---------|
|  Socket Reducer M&F | 724.100.90 | 100 x 90 | 85 |
|  Adaptor F&F | 724.90.100 | 90 x 100 | 90 |
|  Inspection Pipe M&F | 129.100 | 100 | 9 |
|  Screw Cap and Base M | 736.90## | 90 | 100 |
| | 136.100 | 100 | 35 |
| | 736C.90 | 90 | 100 |
| | 136C.100* | 100 | 85 |
| | 736G.90** | 90 | 1 |
| | *Cap only **Gasket only - use with 736.90 cap ## Use with 736G.90 Gasket - sold separately | | |

| | Order Code | Size (mm) | Ctn Qty |
|--|---|-----------|---------|
|  Push-on Cap | 737.90 | 90 | 300 |
| | 137.100 | 100 | 135 |
| | 137.150 | 150 | 68 |
|  Pipe Clip | 140.90 | 90 | 100 |
|  Kerb Outlet Adaptor | 765.90 | 90 | 28 |
| | 765.100 | 100 | 18 |
|  Stormwater Grate Dual Size Outlet | 769.90 ** | 90 | 150 |
| | 769.150.100*** | 150 x 100 | 28 |
|  Stormwater Grate Insert | 769.150G | 150 | 1 |
| | Replacement grate insert for 769.150.100 Stormwater Grate | | |

Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex stormwater fittings may be subject to change without notice.

NOTES



PLUMBING, DRAIN, WASTE & VENT SYSTEMS

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX NOVADRAIN® PVC-U DWV PIPE - NON PRESSURE APPLICATIONS ONLY - AS/NZS 1260


NOVADRAIN® PVC-U DWV PIPE SOLVENT CEMENT JOINT & PLAIN END

| | Order Code | Size (mm) x Length (mm) | Pack Qty |
|---|--------------|-------------------------|----------|
|  | 100.32.6 SOE | 32 x 6 | 240/10* |
| | 100.40.6 SOE | 40 x 6 | 180/10* |
| | 100.50.6 SOE | 50 x 6 | 150/5* |
| | 100.65.6 SOE | 65 x 6 | 102 |
| | 100.80.4 PE | 80 x 4 | 88 |
| | 100.80.6 SOE | 80 x 6 | 88 |

Solvent Cement Joint

*These bundle sizes are the minimum order quantity

NOVADRAIN® 4000 PVC-U DWV PIPE SOLVENT CEMENT JOINT & RUBBER RING JOINT - SN4

| | Order Code | Size (mm) x Length (mm) | Pack Qty |
|---|------------------|-------------------------|----------|
|  | 100SN4.150.6 SOE | 150 x 6 | 28 |
| | Z100SN4.150.3 | 150 x 3 | 28 |
| | Z100SN4.150.4 | 150 x 4 | 28 |
| | Z100SN4.150.6 | 150 x 6 | 28 |
| | Z100SN4.175.6 | 175 x 6 | 20 |
| | Z100SN4.225.6 | 225 x 6 | 12 |
| | Z100SN4.300.6 | 300 x 6 | 6 |
| | Z100SN4.375.6 | 375 x 6 | 6 |
| | Z100SN4.475.6 | 475 x 6 | 2 |
| | Z100SN4.600.6# | 600 x 6 | 2 |

Solvent Cement & Rubber Ring Joint

Not necessarily held stock and may be subject to minimum production quantities, manufacturing lead times and tooling availability.

NOVADRAIN® 6000 PVC-U DWV PIPE SOLVENT CEMENT JOINT & RUBBER RING JOINT - SN6

| | Order Code | Size (mm) x Length (mm) | Pack Qty |
|---|------------------|-------------------------|----------|
|  | 100SN6.100.6 SOE | 100 x 6 | 67 |
| | 100SN6.100.6 RRJ | 100 x 6 | 67 |

Solvent Cement & Rubber Ring Joint

Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex plumbing, drain, waste and vent fittings may be subject to change without notice.

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX NOVADRAIN® PVC-U DWV PIPE - NON PRESSURE APPLICATIONS ONLY AS/NZS 1260


NOVADRAIN® 8000 PVC-U DWV PIPE RUBBER RING JOINT - SN8

| | Order Code | Size (mm) x Length (mm) | Pack Qty |
|---|----------------|-------------------------|----------|
|  | Z100SN8.150.3 | 150 x 3 | 28 |
| | Z100SN8.150.4 | 150 x 4 | 28 |
| | Z100SN8.150.6 | 150 x 6 | 28 |
| | Z100SN8.175.6 | 175 x 6 | 20 |
| | Z100SN8.225.3 | 225 x 3 | 12 |
| | Z100SN8.225.4 | 225 x 4 | 12 |
| | Z100SN8.225.6 | 225 x 6 | 12 |
| | Z100SN8.300.3 | 300 x 3 | 6 |
| | Z100SN8.300.4 | 300 x 4 | 6 |
| | Z100SN8.300.6 | 300 x 6 | 6 |
| | Z100SN8.375.3 | 375 x 3 | 6 |
| | Z100SN8.375.4 | 375 x 4 | 6 |
| | Z100SN8.375.6 | 375 x 6 | 6 |
| | Z100SN8.475.6 | 475 x 6 | 2 |
| | Z100SN8.600.6# | 600 x 6 | 2 |

Rubber Ring Joint

Not necessarily held stock and may be subject to minimum production quantities, manufacturing lead times and tooling availability.

NOVADRAIN® 10000 PVC-U DWV PIPE RUBBER RING JOINT - SN10

| | Order Code | Size (mm) x Length (mm) | Pack Qty |
|---|-------------------|-------------------------|----------|
|  | 100SN10.100.6 RRJ | 100 x 6 | 67 |

Rubber Ring Joint

NOVADRAIN® 16000 PVC-U DWV PIPE RUBBER RING JOINT - SN16

| | Order Code | Size (mm) x Length (mm) | Pack Qty |
|---|-------------------|-------------------------|----------|
|  | 100SN16.100.6 RRJ | 100 x 6 | 67 |
| | Z100SN16.150.3 | 150 x 3 | 28 |
| | Z100SN16.150.4 | 150 x 4 | 28 |
| | Z100SN16.150.6 | 150 x 6 | 28 |
| | Z100SN16.175.4 | 175x4 | 20 |
| | Z100SN16.175.6 | 175 x 6 | 20 |
| | Z100SN16.225.3 | 225 x 3 | 12 |
| | Z100SN16.225.4 | 225 x 4 | 12 |
| | Z100SN16.225.6 | 225x6 | 12 |
| | Z100SN16.300.3 | 300 x 3 | 6 |
| | Z100SN16.300.4 | 300 x 4 | 6 |
| | Z100SN16.300.6 | 300x6 | 6 |
| | Z100SN16.375.3 | 375 x 3 | 6 |
| | Z100SN16.375.4 | 375 x 4 | 6 |
| | Z100SN16.375.6 | 375x6 | 6 |
| | Z100SN16.475.3 | 475 x 3 | 2 |
| | Z100SN16.475.4 | 475 x 4 | 2 |
| | Z100SN16.475.6 | 475x6 | 2 |

Rubber Ring Joint

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX RESTRAIN® PVC-U DWV PIPE FOR TRENCHLESS INSTALLATION NON-PRESSURE APPLICATIONS ONLY - AS/NZS 1260

RESTRAIN® PVC-U THREADED JOINT DWV PIPE SN16



| | Order Code | Size (mm) x Length (mm) | Pack Qty |
|--|---------------|-------------------------|----------|
| | RESTRAIN100.1 | 100 x 1 | 67 |
| | RESTRAIN100.2 | 100 x 2 | 67 |
| | RESTRAIN100.3 | 100 x 3 | 67 |
| | RESTRAIN150.1 | 150 x 1 | 28 |
| | RESTRAIN150.2 | 150 x 2 | 28 |
| | RESTRAIN150.3 | 150 x 3 | 28 |
| | RESTRAIN225.1 | 225 x 1 | 12 |
| | RESTRAIN225.2 | 225 x 2 | 12 |
| | RESTRAIN225.3 | 225 x 3 | 12 |
| | RESTRAIN300.1 | 300 x 1 | 6 |
| | RESTRAIN300.2 | 300 x 2 | 6 |
| | RESTRAIN300.3 | 300 x 3 | 6 |
| | RESTRAIN375.1 | 375 x 1 | 6 |
| | RESTRAIN375.2 | 375 x 2 | 6 |
| | RESTRAIN375.3 | 375 x 3 | 6 |

Threaded Joint with Seal Ring

All RESTRAIN® products are made to order.
Contact Iplex Pipelines for availability of alternative length options.

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX NOVADRAIN® PVC-U DWV FITTINGS SCJ NON-PRESSURE-AS / NZS 1260

NOTE: THE BAG QUANTITY SHOWN IS THE MINIMUM ORDER QUANTITY FOR 32MM, 40MM & 50MM DWV FITTINGS

| | Order Code | Size (mm) | Ctn/Bag Qty |
|---|------------|---------------------|-------------|
|  | 101.32.15 | 32 x 15° | 200 / 10 |
| | 101.32.45 | 32 x 45° | 160 / 5 |
| | 101.32.88 | 32 x 88° | 120 / 5 |
| | 101.40.15 | 40 x 15° | 60 / 10 |
| | 101.40.43 | 40 x 43° | 100 / 10 |
| | 101.40.60 | 40 x 60° | 200 / 5 |
| | 101.40.88 | 40 x 88° | 80 / 10 |
|  | 101.50.15 | 50 x 15° | 35 / 5 |
| | 101.50.45 | 50 x 45° | 55 / 5 |
| | 101.50.88 | 50 x 88° | 40 / 10 |
| | 101.65.15 | 65 x 15° | 140 |
| | 101.65.45 | 65 x 45° | 120 |
| | 101.65.88 | 65 x 88° | 70 |
| | 101.80.15 | 80 x 15° | 70 |
|  | 101.80.45 | 80 x 45° | 60 |
| | 101.80.88 | 80 x 88° | 40 |
| | 101.100.5 | 100 x 5° | 42 |
| | 101.100.15 | 100 x 15° | 35 |
| | 101.100.30 | 100 x 30° | 33 |
| | 101.100.45 | 100 x 45° | 32 |
| | 101.100.60 | 100 x 60° | 27 |
| Plain Bend F&F | 101.100.88 | 100 x 88° | 19 |
| | 101.150.15 | 150 x 15° | 12 |
| | 101.150.45 | 150 x 45° | 9 |
|  | 101.150.88 | 150 x 88° | 5 |
| | | | |
| Expansion Swivel Joint F&F | 101.100.A | 100 x 0°-40° x 52mm | 8/1 |
|  | | | |
| | 101.150A | 150 x 0°-45° | 7 |
| Adjustable Bend F&F | | | |

Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex plumbing, drain, waste and vent fittings may be subject to change without notice.


SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX NOVADRAIN®

PVC-U DWV FITTINGS SCJ NON-PRESSURE-AS / NZS 1260

| | Order Code | Size (mm) x Length (mm) | Ctn Qty |
|---|------------------|-------------------------------|------------|
|  | 171.40.42 | 40 x 42° | 60 / 10 |
| | 171.40.88 | 40 x 88° | 80 / 10 |
|  | 171.50.42 | 50 x 42° | 50 / 10 |
| | 171.50.88 | 50 x 88° | 40 / 10 |
|  | 171.65.43 | 65 x 43° | 85 |
| | 171.80.42 | 80 x 42° | 60 |
|  | 171.80.88 | 80 x 88° | 50 |
| | 171.100.5 | 100 x 5° | 45 |
|  | 171.100.11 | 100 x 11° | 36 |
| | 171.100.15 | 100 x 15° | 35 |
|  | 171.100.22 | 100 x 22° | 28 |
| | 171.100.30 | 100 x 30° | 34 |
|  | 171.100.43 | 100 x 43° | 30 |
| | 171.100.60 | 100 x 60° | 27 |
|  | 171.100.88 | 100 x 88° | 19 |
| | 171.150.42 | 150 x 42° | 9 |
| Plain Bend M&F | 171.150.88 | 150 x 88° | 5 |
|  | 171.50.40.42 | 50* x 40 x 42° | 50 / 5 |
| | * Spigot is 50mm | | |

| | Order Code | Size (mm) x Length (mm) | Ctn Qty |
|--|-------------|-------------------------------|------------|
|  | 101.40.45W | 40 x 45° | 60 / 5 |
| | 101.40.88W | 40 x 88° | 40 / 10 |
| | 101.50.45W | 50 x 45° | 90 / 5 |
| | 101.50.88W | 50 x 88° | 70 / 10 |
| | 101.65.88W | 65 x 88° | 60 |
| | 101.80.88W | 80 x 88° | 35 |
| | 101.100.45W | 100 x 45° | 28 |
| | 101.100.88W | 100 x 88° | 17 |

Inspection Bend F&F







Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex plumbing, drain, waste and vent fittings may be subject to change without notice.

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX NOVADRAIN®

PVC-U DWV FITTINGS SCJ NON-PRESSURE-AS / NZS 1260





| | Order Code | Size (mm) | Ctn/ Bag Qty |
|---|---|--------------------|--------------------|
|  | 102.100.88 | 100 x 88° | 15 |
| Rear Access Bend F&F | | | |
|  | 103.100.45 | 100 x 45° | 8 |
| 45° | | | |
|  | 103.100.88 | 100 x 88° | 8 |
| 88° | | | |
| Side Access Bend F&F | | | |
|  | 104.32.88 | 32 x 88° | 40/5 |
| 45° | 104.40.45 | 40 x 45° | 35/5 |
| | 104.40.88 | 40 x 88° | 50/5 |
| | 104.50.45 | 50 x 45° | 25/5 |
| | 104.50.88 | 50 x 88° | 50/5 |
| | 104.65.45 | 65 x 45° | 35 |
| | 104.65.88 | 65 x 88° | 45 |
| | 104.80.45 | 80 x 45° | 24 |
| 88° | 104.80.88 | 80 x 88° | 24 |
| | 104.100.45** | 100 x 45° | 12 |
| | 104.100.88*** | 100 x 88° | 14 |
| | 104.150.45* | 150 x 45° | 3 |
| | 104.150.88 | 150 x 88° | 4 |
| Plain Junction F&F&F | *Threaded branch **Threaded Inlet mainway *** Threaded Inlet mainway and branch | | |
|  | 104.80.50.45 | 80 x 40 x 45° | 32 |
| 45° | 104.100.50.45 | 100 x 50 x 45° | 18 |
| | 104.100.50.88 | 100 x 50 x 88° | 24 |
| | 104.100.65.45 | 100 x 65 x 45° | 18 |
| 88° | 104.100.80.45 | 100 x 80 x 45° | 16 |
| | 104.150.100.45* | 150 x 100 x 45° | 5 |
| Reducing Junction F&F&F | 104.150.100.88 | 150 x 100 x 88° | 5 |
| | *Threaded branch | | |
|  | 104.100.15 LH | 100 x 45° x 150 LH | 9/1 |
| 100 x 45° x 15° Drop Junction F&F&F | 104.100.15 RH | 100 x 45° x 150 RH | 9/1 |







| | Order Code | Size (mm) | Ctn/ Bag Qty |
|--|-------------------|-----------|--------------------|
|  | 104.40.88W | 40 | 40/5 |
| Inspection Junction F&F&F | 104.50.88W | 50 | 40/5 |
| | 104.65.88W | 65 | 40 |
| | 104.80.88W | 80 | 20 |
| | 104.100.88W | 100 | 12 |
|  | 105.100.88 | 100 x 88° | 10 |
| Rear Access Junction F&F&F | | | |
|  | 105.100.45LH | 100 x 45° | 7 |
| LH | | | |
|  | 105.100.45RH | 100 x 45° | 7 |
| RH | | | |
| Side Access Junction F&F&F | | | |
|  | 106.100.88 | 100 x 88° | 8 |
| Double Junction F&F&F&F | | | |
| | 110.32 | 32 | 200/5 |
| | 110.40 | 40 | 60/10 |
| | 110.50 | 50 | 130/10 |
|  | 110.65 | 65 | 130 |
| Straight Coupling F&F | 110.80 | 80 | 96 |
| | 110.100 | 100 | 45 |
|  | 110.100T* | 100 | 45 |
| Straight Coupling F&F Threaded One End | 110.150 | 150 | 12 |
| | 110.150T* | 150 | 12 |
| | *Threaded one end | | |

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX NOVADRAIN® PVC-U DWV FITTINGS SCJ NON-PRESSURE-AS / NZS 1260

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|---|---|-----------|--------------------|
|  Expansion Coupling F&F | 111.40 | 40 | 40/5 |
| | 111.50 | 50 | 50/5 |
| | 111.65 | 65 | 105 |
| | 111.80 | 80 | 50 |
| | 111.100 | 100 | 36 |
| | 111.150 | 150 | 12 |
|  Female Iron to PVC Socket F&F | 112.32 | 32 | 80/5 |
| | 112.40 | 40 | 60/10 |
| | 112.50 | 50 | 80/10 |
| | 112.65 | 65 | 30 |
|  Male Iron to PVC Socket M&F | 113.32 | 32 | 80/5 |
| | 113.40 | 40 | 90/10 |
| | 113.50 | 50 | 100/10 |
| | 113.100 | 100 | 12 |
| | 114.32* | 32 | 100/10 |
|  Copper to PVC Adaptor F&F | 114.40* | 40 | 180/10 |
| | 114.50* | 50 | 110/5 |
| | 114.100* | 100 | 36 |
| | * Compatible with NZS or BS copper tube | | |

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|---|-------------------|-----------|--------------------|
|  Strap on Boss F | 119.100.50 | 100 x 50 | 70 |
| | 120.80 | 80 | 60 |
|  Bolted Trap Screw (Socket) F | 120.100 | 100 | 30 |
| | 121.100 | 100 | 17 |
|  Bolted Trap Screw M (Spigot Into Pipe Bore) | 198.65.40 | 65 x 40 | 65 |
| | 198.65.50 | 65 x 50 | 65 |
| | 198.100.40 | 100 x 40 | 36 |
|  Pipe Reducer M (Spigot Into Pipe Bore) | 122.100.50 | 100 x 50 | 72 |
| | 123.40.32 | 40 x 32 | 90/5 |
|  Level Invert Taper M&F | 123.50.40 | 50 x 40 | 50/10 |
| | 123.65.40 | 65 x 40 | 180 |
| | 123.65.50 | 65 x 50 | 200 |
| | 123.80.50 | 80 x 50 | 85 |
| | 123.80.65 | 80 x 65 | 85 |
| | 123.100.50 | 100 x 50 | 22 |
| | 123.100.65 | 100 x 65 | 60 |
| | 123.100.80 | 100 x 80 | 45 |
| | 123.150.100 | 150 x 100 | 20 |
| | 123.150.100S* | 150 x 100 | 1 |
|  Level Invert Taper F&F | *Socket both ends | | |





Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex plumbing, drain, waste and vent fittings may be subject to change without notice.








SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX NOVADRAIN®

PVC-U DWV FITTINGS SCJ NON-PRESSURE-AS / NZS 1260

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|--|---|-----------|--------------------|
|  <p>Socket Reducer M&F</p> | 124.40.32 | 40 x 32 | 130/5 |
| | 124.50.40 | 50 x 40 | 100/10 |
| | 124.65.40 | 65 x 40 | 180/10 |
| | 124.65.50 | 65 x 50 | 200/10 |
| | 124.80.50 | 80 x 50 | 130/10 |
| | 124.80.65 | 80 x 65 | 80 |
| | 124.100.40 | 100 x 40 | 87 |
| | 124.100.50 | 100 x 50 | 87 |
| | 124.100.65 | 100 x 65 | 87 |
| | 124.100.80 | 100 x 80 | 84 |
| 124.150.100 | 150 x 100 | 35 | |
|  <p>Ceramic Socket to PVC Spigot Adaptor</p> | 124.AC.100 | 140 x 100 | 72 |
| | 124.AC.150 | 192 x 150 | 8 |
|  <p>Floor Flange</p> | 125.65 | 65 | 300/10 |
| | 125.80 | 80 | 250 |
| | 125.100 | 100 | 160 |
|  <p>Female Pan Collar (Offset)</p> | 127.80* | 80 | 36 |
| | *Offset | | |
|  <p>Male Pan Collar (Offset or Concentric)</p> | 127.100** | 100 | 36 |
| | 127.100A* | 100 | 36 |
| | 127.100R*** | 100 | 140 |
| | *Offset ** Concentric *** Rubber Seal Ring only | | |


| | Order Code | Size (mm) | Ctn/ Bag Qty |
|--|---|-----------|--------------------|
|  <p>Safe Waste Tray</p> | 128.100 | 100 | 120 |
| | 129.100* | 100 | 9 |
| | 129.100S** | 100 | 14 |
|  <p>Inspection Pipe M&F</p> | 129.150**** | 150 | 4 |
| | * Nominal 150mm Access opening with access lid ** Nominal 100mm Access opening with threaded screw cap and body threaded on one main way socket *** Nominal 150mm Access opening with threaded screw cap and body threaded on one main way socket | | |
| | **** | | |
|  <p>Inspection Pipe F&F</p> | 129.80 | 80 | 28 |
| | 129.100FF** | 100 | 9 |
| | 129.150FF** | 150 | 4 |
| **Nominal 150mm Access opening | | | |
|  <p>Weather Apron</p> | 131.50 | 50 | 50/5 |
| | 131.65 | 65 | 60 |
| | 131.80 | 80 | 156 |
| | 131.100 | 100 | 100 |
| | 136.40 | 40 | 260 |
|  <p>Threaded Access Cap and Base</p> | 136.50 | 50 | 90 |
| | 136.80 | 80 | 80 |
| | 136.100 | 100 | 35 |
| | 136.150 | 150 | 12 |
| | 136C.100 | 100 | 45 |
|  <p>Threaded Access Cap</p> | 136C.150 | 150 | 24 |
| | 136L.150* | 150 | 1 |
|  <p>150mm Access Lid</p> | * Nominal 150mm non- threaded access lid only, for 129 inspection pipe & 105 access junction | | |

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX NOVADRAIN®

PVC-U DWV FITTINGS SCJ NON-PRESSURE-AS / NZS 1260

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|---|------------|---|--|
|  Push-on Dust Cap | 136.100PP | 100 | 250 |
|  Push-on Cap | 137.40 | 40 | 120/10 |
| | 137.50 | 50 | 100/10 |
| | 137.65 | 65 | 250/10 |
| | 137.80 | 80 | 160/10 |
| | 137.100 | 100 | 60 |
| | 137.150 | 150 | 64 |
| | 137.300 | 300 | 12/1 |
|  Vent Cowl | 150.40 | 40 | 100/5 |
| | 150.50.40 | 50 x 40 | 40/5 |
| | 150.65 | 65 | 170 |
| | 150.80 | 80 | 72 |
| | 150.100 | 100 | 135 |
| | | | |
|  Squat Floor Waste Gully** | 159.80.50P | 80 x 50 | 32 |
| | 159.80.65P | 80 x 65 | 28 |
| | 159.100.50 | 100 x 50 | 26 |
| | 159.100.65 | 100 x 65 | 22 |
| | | **Use only in conjunction with Iplex Boss Junctions | |
|  Adjustable Gully Trap* | 159.100* | 100 | 10 |
| | | | *Use only in conjunction with Iplex Boss Junctions |

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|--|------------------|---|--------------------|
|  Finishing Collar | 172.100 | 100 | 66 |
|  Pop-out Grate (Flat) | 151.140 | 140 | 132 |
| | | Grate Only Use in conjunction with 172.100 Finishing Collar | |
|  Pop-out Grate (Domed) | 172G.100 | 140 | 130 |
| | | Grate Only Use in conjunction with 172.100 Finishing Collar | |
|  DWV Overflow Relief Cap | 173.100ORC | 100 | 30 |
|  Boss Junction M&F* | 174.80.50.40.88 | 80x(2x50) x(2x40) x88° | 30 |
| | 174.80.5444.88 | 80x(1x50) x(3x40)x88° | 30 |
| | 174.100.50.40.88 | 100x(3x50) x(1x40)x88° | 16 |
| | 174.100.5444.88 | 100x(1x50) x(3x40)x88° | 16 |
| | | *Use only in conjunction with Iplex Squat Floor Gully and Adjustable Gully Trap | |
|  Boss Junction F&F* | 104.100.50.40.88 | 100x(3x50) x(1x40)x88° | 12 |
| | | *Use only in conjunction with Iplex Squat Floor Waste Gully and Adjustable Gully Trap | |


Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex plumbing, drain, waste and vent fittings may be subject to change without notice.

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX NOVADRAIN®

PVC-U DWV FITTINGS SCJ NON-PRESSURE-AS / NZS 1260

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|---|--|-----------|--------------------|
|  Slab Repair Coupling | 178.100 | 100 | 32 |
| | Outlet end fits inside DWV pipe bore to allow repair of DWV vertical riser through concrete floor slab | | |
|  Vermin Stopper | 183.50 | 50 | 210/5 |
|  Copper to PVC Seal Ring | 9145.80 | 80 | 1 |
| | 9145.100 | 100 | 1 |
| | 9145.150 | 150 | 1 |
| | Compatible with NZS or BS Copper Tube | | |










SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX NOVADRAIN®

PVC-U DWV FITTINGS RRJ NON-PRESSURE - AS/NZS 1260

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|---|-------------|-------------|--------------------|
|  Plain Bend F&F | 1501.100.45 | 100 x 45° | 20 |
| | 1501.100.60 | 100 x 60° | 18 |
| | 1501.100.88 | 100 x 88° | 16 |
| | 1501.150.45 | 150 x 45° | 6 |
| | 1501.150.88 | 150 x 88° | 4 |
|  Adjustable Bend F&F | 1501.150A | 150 x 0-45° | 6 |
|  Plain Bend M&F | 1571.100.5 | 100 x 5° | 32 |
| | 1571.100.11 | 100 x 11° | 34 |
| | 1571.100.15 | 100 x 15° | 27 |
| | 1571.100.22 | 100 x 22° | 24 |
| | 1571.100.30 | 100 x 30° | 27 |
| | 1571.150.15 | 150 x 15° | 10 |
|  Ramp Bend F&F | 1502.100.88 | 100 x 88° | 12 |
|  Access Bend 45° F&F | 1503.100.45 | 100 x 45° | 8 |
|  Access Bend 88° F&F | 1503.100.88 | 100 x 88° | 8 |

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|--|-----------------|-----------------|--------------------|
|  45° Plain Junction F&F | 1504.100.45 | 100 x 45° | 8 |
|  88° Plain Junction F&F | 1504.100.88 | 100 x 88° | 9 |
|  150mm 45° Plain Junction F&F | 1504.150.45 | 150 x 45° | 2 |
|  150mm 88° Plain Junction M&F | 1574.150.88 | 150 x 88° | 2 |
|  150mm 45° Reducing Junction F&F | 1504.150.100.45 | 150 x 100 x 45° | 3 |
|  150mm 45° Reducing Junction M&F | 1574.150.100.45 | 150 x 100 x 45° | 3 |
|  150mm 88° Reducing Junction M&F | 1574.150.100.88 | 150 x 100 x 88° | 5 |
|  100mm 45° LH Access Junction F&F | 1505.100.45LH | 100 x 45° | 6 |
|  100mm 45° RH Access Junction F&F | 1505.100.45RH | 100 x 45° | 6 |

Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex plumbing, drain, waste and vent fittings may be subject to change without notice.

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLX NOVADRAIN®

PVC-U DWV FITTINGS RRJ NON-PRESSURE - AS/NZS 1260










| | Order Code | Size (mm) | Ctn/ Bag Qty |
|--|--------------|-----------|--------------------|
|  Slip Coupling F&F | 1511S.80 | 80 | 45 |
| | 1511S.150 | 150 | 12 |
|  Combination Loose/ Slip Coupling F&F | 1511.100 | 100 | 36 |
|  Loose Coupling F&F | 1511.150 | 150 | 12 |
|  Repair Coupling | 1511R.100 | 100 | 27 |
|  Fresh Air Inlet | 1516.100 | 100 | 12 |
|  Level Invert Taper | 1523.150.100 | 150 x 100 | 15 |
|  Reverse Level Invert Taper | 1527.100.150 | 100 x 150 | 18 |
|  PVC to Ceramic Adaptor 100mm | 1524.100 | 100 | 44 |
|  Ceramic Socket to PVC Adaptor | 1525.100 | 100 | 36 |
| | 1525.150 | 150 | 10 |

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|--|--------------|-----------|--------------------|
|  Inspection Pipe M&F | 1529.100 | 100 | 9 |
| | 1529.150 | 150 | 4 |
|  Gulley Trap F&F | 1559.100 | 100 | 6 |
|  Gulley Dish | 1575.100 | 100 | 10 |
| | 1575L.100* | 100 | 45 |
| | *Lid Only | | |
|  Gulley Dish Riser | 1575.100R | 100 | 4 |
| | 1575.200R | 200 | 12 |
| | 1575.300R | 300 | 4 |
|  Reflux Valve F&F | 1588.100 | 100 | 2 |
|  Flap Valve Assembly Only | 1588.100FLAP | 100 | 1 |

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX® WASTE TRAPS, PAN CONNECTORS & PAN BENDS

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|---|-------------|-----------|--------------------|
|  Plain P Trap | 160.40.32P | 40 x 32 | 22 |
| | 160.50P | 50 x 32 | 30 |
|  Combination S&P (Includes Dishwasher Connection) | 162.40.32DW | 40 x 32 | 45 |
|  Waste Trap S&P | PS32.40C | 40 x 32 | 1 |
|  Waste Trap Telescopic S&P | PS32.40TR | 40 x 32 | 1 |
|  Waste Trap Telescopic with Nipple S&P | PS32.40TS | 40 x 32 | 1 |
|  Waste Trap with Nipple S&P | PS32.40S | 40 x 32 | 1 |
|  Waste Trap Telescopic AAV with Nipple S&P | PS32.40CVTS | 40 x 32 | 1 |
|  Waste Trap Telescopic P | PS32.40TP | 40 x 32 | 1 |
|  Waste Trap Short P | PS32.40P | 40 x 32 | 1 |
|  Waste Trap Telescopic with Nipple P | PS32.40NP | 40 x 32 | 1 |
|  Waste Trap Telescopic Pop-up S&P | PS32.40PU | 40 x 32 | 1 |
|  Waste Trap Telescopic Pop-up AAV S&P | PS32.40PUV | 40 x 32 | 1 |







| | Order Code | Size (mm) | Ctn/ Bag Qty |
|---|-------------|-----------|--------------------|
|  Waste Trap Telescopic Plug & Waste S&P | PS32.40PW | 40 x 32 | 1 |
|  Waste Trap Telescopic Plug & Waste AAV S&P | PS32.40PWW | 40 x 32 | 45 |
|  Waste Trap Telescopic AAV S&P | PS32.40VTR | 40 x 32 | 1 |
|  Pan Connector 80mm Long Spigot Concentric | PCW80 | 80 | 1 |
|  Pan Bend | FFPB100 | 100 | 1 |
|  Pan Bend with Bracket | FFPB100BK | 100 | 1 |
|  Adjustable Extended Pan Bend with Bracket | FFPB100EXT | 100 | 1 |
|  Pan Bend Q with Bracket | FFPBQ100EXT | 100 | 1 |
|  Pan Bend Universal with Bracket | FFPB100EXT | 100 | 1 |
|  Trap Adapter 32 x 40mm | TA4032 | 32 x 40 | 1 |
|  Trap Adapter 40mm | TA4040 | 40 x 40 | 1 |
|  Waste Extension Double with Nipple | DWA40 | 40 x 40 | 1 |
|  Low Level Basin Trap with Plug & Waste 40mm | LLBTD | 40 x 40 | 1 |
|  Low Level Basin Trap with Pop-Up 40mm | LLBTR | 40 x 40 | 1 |

SECTION 4

PLUMBING, DRAIN, WASTE & VENT SYSTEMS

IPLEX® PIPE SUPPORT CLIPS

FOR USE WITH IPLEX® PVC-U DWV PIPES

| | Order Code | Size (mm) | Ctn/ Bag Qty |
|---|------------|----------------------|--------------------|
|  DWV Pipe Clip | 140.32 | 32 | 540/10 |
| | 140.40 | 40 | 400/10 |
| | 140.50 | 50 | 240/5 |
| | 140.65 | 65 | 80 |
|  DWV Holderbat (Aluminium) | 140H.80 | 80 | 100 |
| | 140H.100 | 100 | 100 |
| | 140H.150 | 150 | 100 |
|  DWV Standard Key Clip | 141.32 | 32 | 300/10 |
| | 141.40 | 40 | 250/10 |
| | 141.50 | 50 | 190/10 |
| | 141.80 | 80 | 50 |
| | 141.100 | 100 | 50/10 |
|  DWV Side Hanger Key Clip | 142.32 | 32 | 400/10 |
| | 142.40 | 40 | 400/10 |
| | 142.50 | 50 | 250 /10 |
| | 142.80 | 80 | 120 |
| | 142.100 | 100 | 120 |
|  DWV Stand Off Key Clip | 143.32 | 32 | 250/10 |
| | 143.40 | 40 | 200/10 |
| | 143.50 | 50 | 200/10 |
| | 143.80 | 80 | 50 |
| | 143.100 | 100 | 35 |
| | 143.150 | 150 | 25 |
|  Quick Stick Hanging Bracket | 144.100A | 40-100 x 450 drop | 10 |

Note: In accordance with Iplex policy of continuous product development, the carton/bag quantity, configuration, range, design or external shape of Iplex plumbing, drain, waste and vent fittings may be subject to change without notice.

RAINWATER DOWNPIPE SYSTEMS

SECTION 5

RAINWATER DOWNPIPE SYSTEMS

IPLEX® DOWNPIPE & FITTINGS

| | Order Code | Description | Size (mm) | Ctn/Bag Qty |
|---|--|---|-------------|-------------|
|  | RP65.3SOE White | Downpipe , above ground application, 65mm | 65 x 3m | 192/12* |
| | RP80.3SOE White | Downpipe , above ground application, 80mm | 80 x 3m | 135/9** |
| | * available in bundles of 12 ** available in bundles of 9 | | | |
| | 700SN4.90.6 SOE Grey | Downpipe or stormwater pipe , above* or below ground application, 90mm | 90 x 6m | 81 |
|  | RWB.65.95 White | Socket bend 95° F&F (convertable to M&F) | 65 x 95° | 15 |
| | RWB.80.95 White | Socket bend 95° F&F (convertable to M&F) | 80 x 95° | 15 |
|  | RWB.65.112 White | Socket bend 112° F&F (convertable to M&F) | 65 x 112° | 15 |
| | RWB.80.112 White | Socket bend 112° F&F (convertable to M&F) | 80 x 112° | 10 |
|  | RWJ.65.95 White | Junction F&F&M | 65 x 95° | 15 |
| | RWJ.80.95 White | Junction F&F&M | 80 x 95° | 10 |
|  | DPC.65 White | Pipe support clips | 65mm | 80 |
| | DPC.80 White | Pipe support clips | 80mm | 80/10 |
|  | DPA.65.90 White | Downpipe to stormwater adaptor F&F | 65mm x 90mm | 75 |
| | DPA.80.90 White | Downpipe to stormwater adaptor F&F | 80mm x 90mm | 65 |
|  | RWSOC.65 White | Downpipe socket joiner M&F | 65mm | 55 |
| | RWSOC.80 White | Downpipe socket joiner M&F | 80mm | 35 |
|  | GP.80 White | Gutter pop (Allows 80mm downpipe connection directly to the spouting profile. Cut 80mm round hole and solvent cement flange to inside of spouting.) | 80mm | 130 |
|  | DSC150 White | Downpipe solvent cement (use with white Iplex® PVC downpipe fittings) | 150ml | 10/1 |

Note: Iplex® 65mm and 80 mm PVC-U rainwater downpipes are suitable for above ground applications only. Iplex Superstorm® 90mm, 100mm or 150mm PVC-U stormwater pipes and fittings may be used for underground rainwater pipes or for larger diameter above ground rainwater down pipes.


*** Iplex Superstorm® stormwater pipes and fittings used above ground, must be painted with a pale-coloured UV resistant water based paint system, for weathering protection.**

RURAL SYSTEMS


SECTION 6

RURAL SYSTEMS

IPLEX ALKATHENE™ LDPE PRESSURE PIPE

| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|--|------------|-----------|---------------------|------------------|
|  Black Pipe | 300.15.25 | 15 | 9.7 | 25 |
| | 300.15.50 | 15 | 9.7 | 50 |
| | 300.15.100 | 15 | 9.7 | 100 |
| | 300.15.200 | 15 | 9.7 | 200 |
| | 300.20.25 | 20 | 9 | 25 |
| | 300.20.50 | 20 | 9 | 50 |
| | 300.20.100 | 20 | 9 | 100 |
| | 300.20.200 | 20 | 9 | 200 |
| | 300.25.25 | 25 | 8 | 25 |
| | 300.25.50 | 25 | 8 | 50 |
| | 300.25.100 | 25 | 8 | 100 |
| | 300.25.200 | 25 | 8 | 200 |
| | 300.32.25 | 32 | 7 | 25 |
| | 300.32.50 | 32 | 7 | 50 |
| | 300.32.100 | 32 | 7 | 100 |
| | 300.32.200 | 32 | 7 | 200 |
| | 300.40.25 | 40 | 6 | 25 |
| | 300.40.50 | 40 | 6 | 50 |
| | 300.40.100 | 40 | 6 | 100 |
| | 300.40.200 | 40 | 6 | 200 |
| 300.50.25 | 50 | 5 | 25 | |
| 300.50.50 | 50 | 5 | 50 | |
| 300.50.100 | 50 | 5 | 100 | |
| 300.50.200 | 50 | 5 | 200 | |

IRRIPOD PIPE LDPE PASTURE IRRIGATION PRESSURE PIPE

| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|--|--------------|-----------|---------------------|------------------|
|  Black Pipe | IRRIPOD45100 | 45 | 5 | 100 |
| | IRRIPOD45200 | 45 | 5 | 200 |


SECTION 6 RURAL SYSTEMS

IPLEX® EFFLUENT PVC-U PRESSURE PIPE


| | Order Code | Size (mm) x Length (m) | Pressure Rating Bar | Pack/Bundle Qty |
|---|---------------------|------------------------|---------------------|-----------------|
|  <p>Lilac Pipe with Rubber Ring Joint</p> | Z822.80PN6.6 LILAC | 80 x 6 | 6 | 60 |
| | Z822.100PN6.6 LILAC | 100 x 6 | 6 | 40 |
| | Z822.80PN8.6 LILAC | 80 x 6 | 8 | 60 |
| | Z822.80PN8.6 LILAC | 100 x 6 | 8 | 40 |

IPLEX® EFFLUENT PE100 PRESSURE PIPE - AS/NZS 4130


IPLEX® EFFLUENT PE PN6.3

| | Order Code | Size (mm) | Pressure Rating Bar | Coil Length in m |
|---|------------------|-----------|---------------------|------------------|
|  <p>Black Pipe with Lilac Stripes</p> | 2200.63PN6.3.50 | 63 | 6.3 | 50 |
| | 2200.63PN6.3.100 | 63 | 6.3 | 100 |
| | 2200.75PN6.3.50 | 75 | 6.3 | 50 |
| | 2200.75PN6.3.100 | 75 | 6.3 | 100 |
| | 2200.90PN6.3.50 | 90 | 6.3 | 50 |
| | 2200.90PN6.3.100 | 90 | 6.3 | 100 |

IPLEX® EFFLUENT PE PN8

| | Order Code | Size (mm) | Pressure Rating Bar | Coil Length in m |
|---|-----------------|-----------|---------------------|------------------|
|  <p>Black Pipe with Lilac Stripes</p> | 2200.75PN8.50 | 75 | 8 | 50 |
| | 2200.75PN8.100 | 75 | 8 | 100 |
| | 2200.90PN8.50 | 90 | 8 | 50 |
| | 2200.90PN8.100 | 90 | 8 | 100 |
| | 2200.110PN8.50 | 110 | 8 | 50 |
| | 2200.110PN8.100 | 110 | 8 | 100 |


IPLEX NOVATUBE™ LDPE HORTICULTURAL LATERAL TUBE


| | Order Code | Size (mm) | Pressure Rating Bar | Coil Length in m |
|--|------------|-----------|---------------------|------------------|
|  <p>Black Pipe</p> | 350.13.50 | 13 | 5 | 50 |
| | 350.13.100 | 13 | 5 | 100 |
| | 350.13.400 | 13 | 5 | 400 |
| | 350.16.25 | 16 | 5 | 25 |
| | 350.16.50 | 16 | 5 | 50 |
| | 350.16.100 | 16 | 5 | 100 |
| | 350.16.400 | 16 | 5 | 400 |
| | 350.19.25 | 19 | 5 | 25 |
| | 350.19.50 | 19 | 5 | 50 |
| | 350.19.100 | 19 | 5 | 100 |
| | 350.19.300 | 19 | 5 | 300 |
| | 350.25.25 | 25 | 5 | 25 |
| | 350.25.50 | 25 | 5 | 50 |
| | 350.25.100 | 25 | 5 | 100 |
| | 350.25.200 | 25 | 5 | 200 |

SECTION 6


RURAL SYSTEMS

IPLEX GREENLINE® PE100 PRESSURE PIPE - AS / NZS 4130


| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|---|---------------|-----------|---------------------|------------------|
|  Black Pipe with Green Stripes | 370.20PN9.50 | 20 | 9 | 50 |
| | 370.20PN9.100 | 20 | 9 | 100 |
| | 370.20PN9.200 | 20 | 9 | 200 |
| | 370.25PN8.50 | 25 | 8 | 50 |
| | 370.25PN8.100 | 25 | 8 | 100 |
| | 370.25PN8.200 | 25 | 8 | 200 |
| | 370.32PN8.50 | 32 | 8 | 50 |
| | 370.32PN8.100 | 32 | 8 | 100 |
| | 370.32PN8.200 | 32 | 8 | 200 |


| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|---|-----------------|-----------|---------------------|------------------|
|  Black Pipe with Green Stripes | 370.40PN6.3.50 | 40 | 6.3 | 50 |
| | 370.40PN6.3.100 | 40 | 6.3 | 100 |
| | 370.40PN6.3.200 | 40 | 6.3 | 200 |
| | 370.50PN6.3.50 | 50 | 6.3 | 50 |
| | 370.50PN6.3.100 | 50 | 6.3 | 100 |
| | 370.50PN6.3.200 | 50 | 6.3 | 200 |
| | 370.63PN6.3.50 | 63 | 6.3 | 50 |
| | 370.63PN6.3.100 | 63 | 6.3 | 100 |
| | 370.63PN6.3.200 | 63 | 6.3 | 200 |

IPLEX FARMLINE™ PE100 PRESSURE PIPE - AS NZS 4130

| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|---|---------------|-----------|---------------------|------------------|
|  Black Pipe with Green Stripes | 365.40PN8.50 | 40 | 8 | 50 |
| | 365.40PN8.100 | 40 | 8 | 100 |
| | 365.40PN8.200 | 40 | 8 | 200 |
| | 365.50PN8.50 | 50 | 8 | 50 |
| | 365.50PN8.100 | 50 | 8 | 100 |
| | 365.50PN8.200 | 50 | 8 | 200 |
| | 365.63PN8.50 | 63 | 8 | 50 |
| | 365.63PN8.100 | 63 | 8 | 100 |
| | 365.63PN8.200 | 63 | 8 | 200 |

IPLEX REDLINE® PE 100 PE100 PRESSURE PIPE - AS NZS 4130


| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|---|------------------|-----------|---------------------|------------------|
|  Black Pipe with Red Stripes | 360.20PN12.5.50 | 20 | 12.5 | 50 |
| | 360.20PN12.5.100 | 20 | 12.5 | 100 |
| | 360.20PN12.5.200 | 20 | 12.5 | 200 |
| | 360.25PN12.5.50 | 25 | 12.5 | 50 |
| | 360.25PN12.5.100 | 25 | 12.5 | 100 |
| | 360.25PN12.5.200 | 25 | 12.5 | 200 |
| | 360.32PN9.50 | 32 | 9 | 50 |
| | 360.32PN9.100 | 32 | 9 | 100 |
| | 360.32PN9.200 | 32 | 9 | 200 |

| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|---|---------------|-----------|---------------------|------------------|
|  Black Pipe with Red Stripes | 360.40PN9.50 | 40 | 9 | 50 |
| | 360.40PN9.100 | 40 | 9 | 100 |
| | 360.40PN9.200 | 40 | 9 | 200 |
| | 360.50PN9.50 | 50 | 9 | 50 |
| | 360.50PN9.100 | 50 | 9 | 100 |
| | 360.50PN9.200 | 50 | 9 | 200 |
| | 360.63PN9.50 | 63 | 9 | 50 |
| | 360.63PN9.100 | 63 | 9 | 100 |
| | 360.63PN9.200 | 63 | 9 | 200 |


SECTION 6


RURAL SYSTEMS

IPLEX RURAL BLACK™ PE100 RISER PRESSURE PIPE - AS / NZS 4130


| | Order Code | Size (mm) | Pressure Rating Bar | Length m |
|---|----------------|-----------|---------------------|----------|
|  Black Pipe | 340.32PN12.5.6 | 32 | 12.5 | 6 |
| | 340.40PN12.5.6 | 40 | 12.5 | 6 |
| | 340.50PN12.5.6 | 50 | 12.5 | 6 |
| | 340.63PN12.5.6 | 63 | 12.5 | 6 |


IPLEX RURAL BLACK™ PE100 PRESSURE PIPE - AS / NZS 4130

| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|---|------------------|-----------|---------------------|------------------|
|  Black Pipe | 340.32PN12.5.50 | 32 | 12.5 | 50 |
| | 340.32PN12.5.100 | 32 | 12.5 | 100 |
| | 340.32PN12.5.200 | 32 | 12.5 | 200 |
| | 340.40PN12.5.50 | 40 | 12.5 | 50 |
| | 340.40PN12.5.100 | 40 | 12.5 | 100 |
| | 340.40PN12.5.200 | 40 | 12.5 | 200 |
| | 340.50PN12.5.50 | 50 | 12.5 | 50 |
| | 340.50PN12.5.100 | 50 | 12.5 | 100 |
| | 340.50PN12.5.200 | 50 | 12.5 | 200 |

| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|--|-------------------|-----------|---------------------|------------------|
|  Black Pipe | 340.63PN12.5.50 | 63 | 12.5 | 50 |
| | 340.63PN12.5.100 | 63 | 12.5 | 100 |
| | 340.63PN12.5.200 | 63 | 12.5 | 200 |
| | 340.75PN12.5.50 | 75 | 12.5 | 50 |
| | 340.75PN12.5.100 | 75 | 12.5 | 100 |
| | 340.90PN12.5.50 | 90 | 12.5 | 50 |
| | 340.90PN12.5.100 | 90 | 12.5 | 100 |
| | 340.110PN12.5.50 | 110 | 12.5 | 50 |
| | 340.110PN12.5.100 | 110 | 12.5 | 100 |

IPLEX BLACKLINE™ PE100 PRESSURE PIPE - AS / NZS 4130


| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|---|--------------------|-----------|---------------------|------------------|
|  Black Pipe with Blue Stripes | 3500.25PN16.25BMS | 25 | 16 | 25 |
| | 3500.25PN16.50BMS | 25 | 16 | 50 |
| | 3500.25PN16.100BMS | 25 | 16 | 100 |
| | 3500.32PN16.25BMS | 32 | 16 | 25 |
| | 3500.32PN16.50BMS | 32 | 16 | 50 |
| | 3500.32PN16.100BMS | 32 | 16 | 100 |
| | 3500.40PN16.25BMS | 40 | 16 | 25 |
| | 3500.40PN16.50BMS | 40 | 16 | 50 |
| | 3500.40PN16.100BMS | 40 | 16 | 100 |
| | 3500.50PN16.25BMS | 50 | 16 | 25 |
| | 3500.50PN16.50BMS | 50 | 16 | 50 |
| | 3500.50PN16.100BMS | 50 | 16 | 100 |

| | Order Code | Size (mm) | Pressure Rating Bar | Coil length in m |
|---|---------------------|-----------|---------------------|------------------|
|  Black Pipe with Blue Stripes | 3500.63PN16.25BMS | 63 | 16 | 25 |
| | 3500.63PN16.50BMS | 63 | 16 | 50 |
| | 3500.63PN16.100BMS | 63 | 16 | 100 |
| | 3500.75PN16.50BMS | 75 | 16 | 50 |
| | 3500.75PN16.100BMS | 75 | 16 | 100 |
| | 3500.90PN16.50BMS | 90 | 16 | 50 |
| | 3500.90PN16.100BMS | 90 | 16 | 100 |
| | 3500.110PN16.50BMS | 110 | 16 | 50 |
| | 3500.110PN16.100BMS | 110 | 16 | 100 |


SECTION 6 RURAL SYSTEMS

IPLEX BLACKLINE™ HP PE100 POLYETHYLENE PRESSURE PIPE - AS / NZS 4130

IPLEX BLACKLINE™ HP PN20



| | Order Code | Size (mm) | Pressure Rating Bar | Coil Length in m |
|--|-------------------|-----------|---------------------|------------------|
|  Black Pipe | 3500.63PN20.50B | 63 | 20 | 50 |
| | 3500.63PN20.100B | 63 | 20 | 100 |
| | 3500.90PN20.50B | 90 | 20 | 50 |
| | 3500.90PN20.100B | 90 | 20 | 100 |
| | 3500.110PN20.50B | 110 | 20 | 50 |
| | 3500.110PN20.100B | 110 | 20 | 100 |


IPLEX BLACKLINE™ HP PN25

| | Order Code | Size (mm) | Pressure Rating Bar | Coil Length in m |
|--|-------------------|-----------|---------------------|------------------|
|  Black Pipe | 3500.63PN25.50B | 63 | 25 | 50 |
| | 3500.63PN25.100B | 63 | 25 | 100 |
| | 3500.90PN25.50B | 90 | 25 | 50 |
| | 3500.90PN25.100B | 90 | 25 | 100 |
| | 3500.110PN25.50B | 110 | 25 | 50 |
| | 3500.110PN25.100B | 110 | 25 | 100 |


IPLEX BLACKLINE™ HP DUCTILE IRON (DI) PRESSURE FITTINGS

FOR USE WITH IPLEX BLACKLINE™ HP PN20 AND PN25 PIPE

| | Order Code | Size (mm) | Ctn/Bag Qty |
|---|--------------|-----------|-------------|
|  Ductile Iron Coupling PN25 | VIT905PEC63C | 63 | 12 |
| | VIT905PEC90C | 90 | 6 |
| | DIC110PE | 110 | 4 |
|  Ductile Iron Transition Coupling PN25 | VIT907TC63C | 63 | 14 |
| | DITC90PE | 90 | 10 |
| | DITC110PE | 110 | 6 |

| | Order Code | Size (mm) | Ctn/Bag Qty |
|---|------------|-----------|-------------|
|  Stainless Steel Male Threaded Adaptor PN25 | SSMTA50 | 63 x 2" | 1 |
| | SSMTA80 | 90 x 3" | 1 |
| | SSMTA100 | 110 x 4" | 1 |

Use with DITC transition coupling


| | Order Code | Size (mm) | PCD (mm) | Ctn/Bag Qty |
|--|------------|------------------|----------|-------------|
|  Ductile Iron Universal Flanged Adaptor PN25 | DIUFA50 | 63 x 50 flange | 120-125 | 1 |
| | DIUFA80 | 90 x 80 flange | 150-160 | 1 |
| | DIUFA100 | 110 x 100 flange | 175-191 | 1 |

Use with DITC transition coupling

SECTION 6 RURAL SYSTEMS


IPLEX NEXUSFLO™ HDPE LAND DRAINAGE PIPE

TWIN WALL, SMOOTH BORE, SLOTTED

| | Order Code | Size (mm) | Coil length in m | SN (KN/m ²) |
|--|-------------|-----------|------------------|-------------------------|
|  <p>Black Pipe with Blue Stripe Supplied with Push Fit Coupler</p> | NEXUS11015 | 110 | 15 | 6 |
| | NEXUS11030 | 110 | 30 | 6 |
| | NEXUS11050 | 110 | 50 | 6 |
| | NEXUS110100 | 110 | 100 | 6 |
| | NEXUS110450 | 110 | 450 | 6 |
| | NEXUS16045 | 160 | 45 | 6 |
| | NEXUS160185 | 160 | 185 | 6 |
| | NEXUS2005 | 200 | 5 | 4 |
| | NEXUS20029 | 200 | 29 | 4 |
| | NEXUS200120 | 200 | 120 | 4 |

IPLEX NEXUSCOIL™ HDPE DUCT PIPE

TWIN WALL, SMOOTH BORE, UNSLOTTED

| | Order Code | Size (mm) | Coil length in m | SN (KN/m ²) |
|--|-----------------|-----------|------------------|-------------------------|
|  <p>Black Pipe with Yellow Stripe Supplied with Push Fit Coupler</p> | NEXUSCOIL11015 | 110 | 15 | 6 |
| | NEXUSCOIL11030 | 110 | 30 | 6 |
| | NEXUSCOIL11050 | 110 | 50 | 6 |
| | NEXUSCOIL110100 | 110 | 100 | 6 |
| | NEXUSCOIL110450 | 110 | 450 | 6 |
| | NEXUSCOIL16045 | 160 | 45 | 6 |
| | NEXUSCOIL160185 | 160 | 185 | 6 |
| | NEXUSCOIL20029 | 200 | 29 | 4 |
| | NEXUSCOIL200120 | 200 | 120 | 4 |

IPLEX NOVAFLO® HDPE LAND DRAINAGE PIPE

SINGLE WALL, CORRUGATED BORE, SLOTTED

| | Order Code | Size (mm) | Coil length in m |
|---|-------------|-----------|------------------|
|  <p>Black Pipe Supplied with Push Fit Coupler - Small Coils - Large Coils</p> | 400.065.15* | 65 | 15 |
| | 400.065.30* | 65 | 30 |
| | 400.065.150 | 65 | 150 |
| | 400.110.15 | 110 | 15 |
| | 400.110.30 | 110 | 30 |
| | 400.110.50 | 110 | 50 |

| | Order Code | Size (mm) | Coil length in m |
|--|-----------------------------------|-----------|------------------|
|  <p>Black Pipe Supplied with Push Fit Coupler - Small Coils - Large Coils</p> | 400.110.100 | 110 | 100 |
| | 400.110.450 | 110 | 450 |
| | 400.160.15 | 160 | 15 |
| | 400.160.45 | 160 | 45 |
| | 400.160.185 | 160 | 185 |
| | * Sold only in bundles of 4 coils | | |

* Sold only in bundles of 4 coils

SECTION 6 RURAL SYSTEMS

IPLEX NOVACOIL® HDPE DUCT PIPE

SINGLE WALL, CORRUGATED BORE, UNSLOTTED

| | Order Code | Size (mm) | Coil length in m |
|---|-------------|-----------|------------------|
|  <p>Black Pipe with White Stripe Supplied with Push Fit Coupler</p> | 500.065.15 | 65 | 15 |
| | 500.065.30 | 65 | 30 |
| | 500.065.150 | 65 | 150 |
| | 500.110.15 | 110 | 15 |
| | 500.110.30 | 110 | 30 |
| | 500.110.100 | 110 | 100 |
| | 500.160.15 | 160 | 15 |
| | 500.160.45 | 160 | 45 |



IPLEX NEXUSFLO™ OR IPLEX NOVAFLO® FITTINGS

| | Order Code | Size (mm) | Ctn/Bag Qty |
|---|----------------|-----------|-------------|
|  <p>Junction</p> | 104.65.45 | 65 | 35 |
| | 104.100.45 | 110 | 12 |
| | 704.150.45 | 160 | 4 |
| | 704.150.100.45 | 160 x 110 | 5 |
|  <p>Pipe Coupler</p> | 410.065 | 65 | 195 |
|  <p>Pipe Coupler</p> | 420.110 | 110 | 40 |
| | 420.160 | 160 | 12 |
| | 420.200 | 200 | 10 |
| | 420.250 | 250 | 1 |
|  <p>Level Invert F&F</p> | 123.150.100S | 160 x 110 | 1 |
|  <p>Flexible Push-on Cap Removable Flexible Cap for Pipe End Protection</p> | 430.110 | 110 | 1 |
| | 430.160 | 160 | 1 |


SECTION 6 RURAL SYSTEMS

IPLEX NEXUS® CULVERT HDPE CULVERT PIPE

TWIN WALL, SMOOTH BORE

| | Order Code | Colour | Size (mm) x Length (m) | Pack/Bundle Qty | SN (KN/m ²) |
|--|------------------|-------------------------|------------------------|-----------------|-------------------------|
|  <p>Black Pipe with Brown Stripe, Socket One End for Push Fit Jointing</p> | NEXUSCULVERT1105 | BLACK with BROWN STRIPE | 110 x 5 | 67 | 5 |
| | NEXUSCULVERT1605 | BLACK with BROWN STRIPE | 160 x 5 | 28 | 5 |
| | NEXUSCULVERT2005 | BLACK with BROWN STRIPE | 200 x 5 | 20 | 5 |
| | NEXUSCULVERT2506 | BLACK with NO STRIPE | 250 x 5 | 12 | 5 |
|  <p>Black Pipe with Green Stripe, Socketed One End for Push Fit Jointing</p> | NEXUSCULVERT3156 | BLACK with GREEN STRIPE | 315 x 6 | 6 | 6 |
| | NEXUSCULVERT4006 | BLACK with GREEN STRIPE | 400 x 6 | 2 | 6 |
| | NEXUSCULVERT5006 | BLACK with GREEN STRIPE | 500 x 6 | 2 | 6 |

IPLEX FARMTUFF® PVC-U CULVERT PIPE

| | Order Code | Size (mm) | Ctn/Bag Qty |
|--|---------------|-----------|-------------|
|  <p>Solvent Cement Joint</p> | 550.110.5 SOE | 110 x 5 | 67 |
| | 550.160.5 SOE | 160 x 5 | 28 |
| | 550.200.3 SOE | 200 x 3 | 20 |
| | 550.200.5 SOE | 200 x 5 | 20 |
| | 550.200.6 SOE | 200 x 6 | 20 |
| | 550.250.3 SOE | 250 x 3 | 12 |
| | 550.250.5 SOE | 250 x 5 | 12 |
| | 550.250.6 SOE | 250 x 6 | 12 |
| | 550.315.3 SOE | 315 x 3 | 6 |
| | 550.315.5 SOE | 315 x 5 | 6 |
| | 550.315.6 SOE | 315 x 6 | 6 |
| | 550.400.3 SOE | 400 x 3 | 6 |
| | 550.400.5 SOE | 400 x 5 | 6 |
| | 550.400.6 SOE | 400 x 6 | 6 |
| | 550.500.3 SOE | 500 x 3 | 2 |
| | 550.500.5 SOE | 500 x 5 | 2 |
| | 550.500.6 SOE | 500 x 6 | 2 |


ENERGY & COMMUNICATIONS SYSTEMS

SECTION 7

ENERGY & COMMUNICATIONS SYSTEMS


IPLEX VOLTA® PVC-U RIGID ELECTRICAL CONDUIT

IPLEX VOLTA® PVC-U RIGID ELECTRICAL CONDUIT - (GREY): ABOVE GROUND (T SOLAR) APPLICATIONS
(TO AS/NZS 61386.21)



| Nominal Diameter (mm) | Order Code | **Duty Classification | # Joint Type | Mean Outside Diameter (mm) | Minimum Internal Diameter (mm) | Bundle Qty |
|-----------------------|----------------------|-----------------------|-------------------|----------------------------|--------------------------------|------------|
| 20 | IPLEXVOLTA.20HD.GY.4 | HD4431 | Spigot/Socket SCJ | 19.9 | 16.2 | 1560/10 |
| 25 | IPLEXVOLTA.25HD.GY.4 | HD4431 | Spigot/Socket SCJ | 24.9 | 20.5 | 1100/10 |
| 32 | IPLEXVOLTA.32HD.GY.4 | HD4431 | Spigot/Socket SCJ | 31.9 | 27.0 | 640/10 |
| 40 | IPLEXVOLTA.40HD.GY.4 | HD4431 | Spigot/Socket SCJ | 39.9 | 34.3 | 420/10 |
| 50 | IPLEXVOLTA.50HD.GY.4 | HD4431 | Spigot/Socket SCJ | 49.9 | 43.5 | 280/5 |


IPLEX VOLTA® PVC-U RIGID ELECTRICAL CONDUIT - (ORANGE): BELOW GROUND APPLICATIONS (TO AS/NZS 61386.21)



| Nominal Diameter (mm) | Order Code | **Duty Classification | # Joint Type | Mean Outside Diameter (mm) | Minimum Internal Diameter (mm) | Bundle Qty |
|-----------------------|----------------------|-----------------------|-------------------|----------------------------|--------------------------------|------------|
| 20 | IPLEXVOLTA.20HD.OR.4 | HD4431 | Spigot/Socket SCJ | 19.9 | 16.2 | 1560/10 |
| 25 | IPLEXVOLTA.25HD.OR.4 | HD4431 | Spigot/Socket SCJ | 24.9 | 20.5 | 1100/10 |
| 32 | IPLEXVOLTA.32HD.OR.4 | HD4431 | Spigot/Socket SCJ | 31.9 | 27.0 | 640/10 |
| 40 | IPLEXVOLTA.40HD.OR.4 | HD4431 | Spigot/Socket SCJ | 39.9 | 34.3 | 420/10 |
| 50 | IPLEXVOLTA.50HD.OR.4 | HD4431 | Spigot/Socket SCJ | 49.9 | 43.5 | 280/5 |

IPLEX VOLTA® PVC-U RIGID ELECTRICAL DUCT

IPLEX VOLTA® PVC-U RIGID ELECTRICAL DUCT - (ORANGE): BELOW GROUND APPLICATIONS (TO AS/NZS 61386.21)




| Nominal Diameter (mm) | Order Code | **Duty Classification | # Joint Type | Mean Outside Diameter (mm) | Minimum Internal Diameter (mm) | Stiffness Class (SN) | Bundle Qty |
|-----------------------|------------------------|-----------------------|-------------------|----------------------------|--------------------------------|----------------------|------------|
| 80 | IPLEXVOLTA.80MD.OR.6 | MD3331 | Spigot/Socket SCJ | 82.5 | 77.1 | n/a | 88/1 |
| 80 | IPLEXVOLTA.80HD.OR.6 | HD4431 | Spigot/Socket SCJ | 82.5 | 75.3 | n/a | 88/1 |
| 100 | IPLEXVOLTA.100MD.OR.6 | MD3331 | Spigot/Socket SCJ | 110.2 | 103.2 | 4 | 67/1 |
| 100 | IPLEXVOLTA.100HD.OR.6 | HD4431 | Spigot/Socket SCJ | 110.2 | 102.0 | 10 | 67/1 |
| 100 | IPLEXVOLTA.100VHD.OR.6 | VHD5531 | Spigot/Socket SCJ | 110.2 | 96.0 | 25 | 67/1 |
| 150 | IPLEXVOLTA.150MD.OR.6 | MD3331 | Spigot/Socket SCJ | 160.3 | 150.4 | 4 | 28/1 |
| 150 | IPLEXVOLTA.150HD.OR.6 | HD4431 | Spigot/Socket SCJ | 160.3 | 148.8 | 10 | 28/1 |
| 150 | IPLEXVOLTA.150VHD.OR.6 | VHD5531 | Spigot/Socket SCJ | 160.3 | 141.4 | 25 | 28/1 |
| 200 | IPLEXVOLTA.200HD.OR.6 | HD4431 | Spigot/Socket SCJ | 225.3 | 210.3 | 10 | 15/1 |

SECTION 6 RURAL SYSTEMS

IPLEX® 2700 SERIES PVC-U RIGID ELECTRICAL DUCT





2700 SERIES PVC-U RIGID ELECTRICAL DUCT - (ORANGE): BELOW GROUND APPLICATIONS (TO AS/NZS 2053.2)

| | Nominal Diameter (mm) | Order Code | **Duty Classification | # Joint Type | Mean Outside Diameter (mm) | Minimum Internal Diameter (mm) | Stiffness Rating (SN) | Bundle Qty |
|---|-----------------------|---------------|-----------------------|-------------------|----------------------------|--------------------------------|-----------------------|------------|
|  | 32** | 2700.32.6 SOE | N/A | Spigot/Socket SCJ | 36.4 | 31.6 | N/A | 240/10 |
| | 40** | 2700.40.6 SOE | N/A | Spigot/Socket SCJ | 42.9 | 37.6 | N/A | 180/10 |
| | 50** | 2700.50.6 SOE | N/A | Spigot/Socket SCJ | 55.8 | 50.5 | N/A | 150/5 |
| | 65** | 2700.65.6 SOE | N/A | Spigot/Socket SCJ | 68.8 | 62.5 | N/A | 102/1 |

**Nominal diameter 32mm, 40mm, 50mm and 65mm PVC-U ducts coloured orange are manufactured to the OD and wall thickness dimensions of AS/NZS 1260.

Note: SN class and Duty Classification are not included in AS/NZS 1260 for these sizes, but these particular size dimensions deliver equivalent mechanical performance in excess of Heavy Duty Classification / SN10.

IPLEX® PVC-U ELECTRICAL BENDS (ORANGE)

| | Order Code | Size (mm/°) |
|---|--------------------|-------------------------|
|  | 2703.50.45R250 | 50 x 45° ROC* 250mm |
| | 4003040.50.45R250 | 50 x 90° ROC* 250mm |
|  | 2703.80.45R250 | 80 x 45° ROC* 250mm |
| | 4003041.50.90R250 | 80 x 90° ROC* 250mm |
|  | 2703.100.45R250 | 100 x 45° ROC* 250mm |
| | 4003042.100.45R250 | 100 x 90° ROC* 250mm |
|  | 2703.100.90R900 | 100 x 90° ROC* 900mm |
| | 2703.100HD.45R350 | 100 x 45° HD ROC* 350mm |
| | 4003043.100.90R250 | 100 x 90° HD ROC* 900mm |

*ROC = Radius of Curvature

SECTION 7

ENERGY & COMMUNICATIONS SYSTEMS

IPLEX® PE FLEXIBLE ELECTRICAL DUCT - COILS

IPLEX® PE FLEXIBLE ELECTRICAL DUCT- FREE STANDING COIL

FREE STANDING COIL



Iplex strongly recommends that mechanical straightening and mechanical re-rounding equipment be used when installing coiled DN 125, 140 and 160 PE duct.

| OD (mm) | Order Code | Colour | Coil Length | SDR Rating | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Maximum safe axial pulling load (KN) |
|---------|----------------------------|----------|-------------|------------|----------------------------|--------------------------|--------------------------------------|
| 32 | Cableduct OR 32/25.200 | ● Orange | 200m | 11 | 32.1 | 3.2 | 2.2 |
| 32 | Cableduct OR 32/25.500 | ● Orange | 500m | 11 | 32.1 | 3.2 | 2.2 |
| 32 | Cableduct OR 32/28.200 | ● Orange | 200m | 17 | 32.1 | 2.0 | 1.5 |
| 32 | Cableduct OR 32/28.500 | ● Orange | 500m | 17 | 32.1 | 2.0 | 1.5 |
| 32 | Cableduct OR 32/27.200 | ● Orange | 200m | 13.6 | 32.1 | 2.6 | 1.8 |
| 40 | Cableduct OR 40/35.100 | ● Orange | 100m | 17 | 40.2 | 2.6 | 2.3 |
| 40 | Cableduct OR 40/35.200 | ● Orange | 200m | 17 | 40.2 | 2.6 | 2.3 |
| 50 | Cableduct OR 50/44.100 | ● Orange | 100m | 17 | 50.3 | 3.2 | 3.7 |
| 50 | Cableduct OR 50/42.100 | ● Orange | 100m | 13.6 | 50.3 | 3.9 | 4.5 |
| 50 | Cableduct OR 50/44.200 | ● Orange | 200m | 17 | 50.3 | 3.2 | 3.7 |
| 50 | Cableduct OR 50/42.200 | ● Orange | 200m | 13.6 | 50.3 | 3.9 | 4.5 |
| 63 | Cableduct OR 63/55.100 | ● Orange | 100m | 17 | 63.3 | 4.0 | 5.8 |
| 63 | Cableduct OR 63/53.100 | ● Orange | 100m | 13.6 | 63.3 | 5.0 | 7.1 |
| 63 | Cableduct OR 63/55.150 | ● Orange | 150m | 17 | 63.3 | 4.0 | 5.8 |
| 90 | Cableduct OR 90/79.50 | ● Orange | 50m | 17 | 90.5 | 5.8 | 12.0 |
| 90 | Cableduct OR 90/79.100 | ● Orange | 100m | 17 | 90.5 | 5.8 | 12.0 |
| 110 | Cableduct OR 110/97.50 | ● Orange | 50m | 17 | 110.5 | 7.0 | 17.8 |
| 110 | Cableduct OR 110/97.100 | ● Orange | 100m | 17 | 110.5 | 7.0 | 17.8 |
| 125 | Cableduct 125/110.100 CXOR | ● Orange | 100m | 17 | 125.5 | 7.8 | 22.8 |
| 140 | Cableduct 140/123.100 CXOR | ● Orange | 100m | 17 | 140.6 | 8.8 | 28.6 |
| 160 | Cableduct 160/140.100 CXOR | ● Orange | 100m | 17 | 160.4 | 10.0 | 37.3 |

IPLEX® PE FLEXIBLE ELECTRICAL DUCT - DRUM COIL

DRUM COIL



| OD (mm) | Order Code | Colour | Coil Length | SDR Rating | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Maximum safe axial pulling load (KN) |
|---------|----------------------------|----------|-------------|------------|----------------------------|--------------------------|--------------------------------------|
| 50 | Cableduct 50/44.800 CXOR | ● Orange | 800m | 17 | 50.3 | 3.2 | 3.7 |
| 50 | Cableduct 50/44.2800 CXOR | ● Orange | 2800m | 17 | 50.3 | 3.2 | 3.7 |
| 110 | Cableduct 110/97.600 CXOR | ● Orange | 600m | 17 | 110.5 | 7.0 | 17.8 |
| 140 | Cableduct 140/123.340 CXOR | ● Orange | 340m | 17 | 140.6 | 8.8 | 28.6 |
| 160 | Cableduct 160/140.270 CXOR | ● Orange | 270m | 17 | 160.4 | 10.0 | 37.3 |

SECTION 6

RURAL SYSTEMS

IPLEX® PE FLEXIBLE ELECTRICAL DUCT - STRAIGHT LENGTHS

IPLEX® PE FLEXIBLE ELECTRICAL DUCT

STRAIGHT LENGTHS



| OD (mm) | Order Code | Colour | Length | SDR Rating | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Maximum Safe Axial Pulling Load (KN) |
|---------|---------------------------|----------|--------|------------|----------------------------|--------------------------|--------------------------------------|
| 110 | Cableduct 110/97.12 CXOR | ● Orange | 12m | 17 | 110.5 | 7.0 | 17.8 |
| 110 | Cableduct 110/97.15 CXOR | ● Orange | 15m | 17 | 110.5 | 7.0 | 17.8 |
| 140 | Cableduct 140/123.12 CXOR | ● Orange | 12m | 17 | 140.6 | 8.8 | 28.6 |
| 140 | Cableduct 140/119.12 CXOR | ● Orange | 12m | 13.6 | 140.6 | 10.3 | 34.7 |
| 140 | Cableduct 140/123.15 CXOR | ● Orange | 15m | 17 | 140.6 | 8.8 | 28.6 |
| 160 | Cableduct 160/130.12 CXOR | ● Orange | 12m | 11 | 160.4 | 14.6 | 55.1 |
| 160 | Cableduct 160/140.12 CXOR | ● Orange | 12m | 17 | 160.4 | 10.0 | 37.3 |
| 160 | Cableduct 160/136.15 CXOR | ● Orange | 15m | 13.6 | 160.4 | 11.8 | 45.3 |
| 160 | Cableduct 160/140.12 CXOR | ● Orange | 12m | 17 | 160.4 | 10.0 | 37.3 |

Iplex strongly recommends that mechanical straightening and mechanical re-rounding equipment be used when installing coiled DN 125, 140 and 160 PE duct.

SECTION 7


ENERGY & COMMUNICATIONS SYSTEMS

IPLEX® PVC-U RIGID COMMUNICATIONS DUCT

CHORUS BRANDED PVC-U RIGID COMMUNICATIONS DUCT

|  | Nominal Diameter (mm) | Order Code | Colour | Duty Classification | Stiffn ss Class | #Joint Type | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Bundle/ Pack QTY |
|---|-----------------------|------------|---------|---------------------|-----------------|-------------------|----------------------------|--------------------------|------------------|
| | 20mm x 6m | 10012937 | ● Green | N/A | N/A | Spigot/Socket SCJ | 26.7 | 1.9 | 150 |
| | 20mm x 6m | 10013281 | ● White | N/A | N/A | Spigot/Socket SCJ | 26.7 | 2.1 | 150 |
| | 50mm x 6m | P4001 | ● Green | N/A | N/A | Rubber Ring Joint | 60.3 | 2.6 | 123 |
| | 100mm x 6m | P4000 | ● Green | SN6 | N/A | Rubber Ring Joint | 110.2 | 3.6 | 67 |

CHORUS BRANDED PVC-U REPAIR SLEEVE FOR COMMUNICATIONS DUCT

|  | Nominal Diameter (mm) | Order Code | Colour | Duty Classification | Stiffn ss Class | #Joint Type | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Bundle/ Pack QTY |
|---|-----------------------|------------|---------|---------------------|-----------------|----------------|----------------------------|--------------------------|------------------|
| | 50mm x 2m | 10013103 | ● Green | N/A | N/A | Plain End, SCJ | 65.6 | 2.6 | 1 |
| | 100mm x 2m | 10013102 | ● Green | N/A | N/A | Plain End, SCJ | 117.3 | 3.6 | 1 |


NON-CHORUS BRANDED PVC-U RIGID COMMUNICATIONS DUCT (GREEN)

|  | Nominal Diameter (mm) | Order Code | Colour | Duty Classification | Stiffn ss Class | #Joint Type | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Bundle/ Pack QTY |
|--|-----------------------|---------------------------|---------|---------------------|-----------------|-------------------|----------------------------|--------------------------|------------------|
| | 20mm x 6m | CD80020 | ● White | N/A | N/A | Spigot/Socket SCJ | 26.7 | 1.7 | 150 |
| | 100mm x 6m | 2780.100.LD.6 SOE | ● Green | LD | SN4 | Spigot/Socket SCJ | 110.2 | 3.6 | 67 |
| | 150mm x 6m | 2780.150.LD.6 SOE | ● Green | LD | SN4 | Spigot/Socket SCJ | 160.3 | 4.1 | 28 |
| | 100mm x 6m | COMMSDUCT.100SN10.HD.GR.6 | ● Green | HD | SN10 | Spigot/Socket SCJ | 110.2 | 3.8 | 67 |
| | 150mm x 6m | COMMSDUCT.150SN10.HD.GR.6 | ● Green | HD | SN10 | Spigot/Socket SCJ | 160.3 | 5.3 | 28 |


NON-CHORUS BRANDED PVC-U RIGID COMMUNICATIONS DUCT (RED)

|  | Nominal Diameter (mm) | Order Code | Colour | Duty Classification | Stiffn ss Class | #Joint Type | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Pack Qty |
|---|-----------------------|----------------------------|--------|---------------------|-----------------|-------------------|----------------------------|--------------------------|----------|
| | 50mm x 6m | 2730.50.6 SOE | ● Red | N/A | N/A | Spigot/Socket SCJ | 55.8 | 2.4 | 150 |
| | 100mm x 6m | 2730.100MD.6 SOE | ● Red | MD | SN4 | Spigot/Socket SCJ | 110.2 | 3.1 | 67 |
| | 100mm x 6m | COMMSDUCT.100SN10.HD.RED.6 | ● Red | HD | SN10 | Spigot/Socket SCJ | 110.2 | 3.8 | 67 |

IPLEX PVC-U RIGID COMMUNICATIONS DUCT (SALMON OR SALMON PINK)

|  | Nominal Diameter (mm) | Order Code | Colour | Duty Classification | Stiffn ss Class | #Joint Type | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Pack Qty |
|---|-----------------------|---------------------------|---------------|---------------------|-----------------|-------------------|----------------------------|--------------------------|----------|
| | 50mm x 6m | COMMSDUCT.50.SAP.6 | ● Salmon Pink | N/A | N/A | Spigot/Socket SCJ | 55.8 | 2.4 | 150 |
| | 50mm x 6m | 2720.50.6 SOE | ● Salmon | N/A | N/A | Spigot/Socket SCJ | 55.8 | 2.4 | 150 |
| | 100mm x 6m | 2720.100MD.6 SOE | ● Salmon | MD | SN4 | Spigot/Socket SCJ | 110.2 | 3.1 | 67 |
| | 100mm x 6m | COMMSDUCT.100SN10.HDSA.6 | ● Salmon | HD | SN10 | Spigot/Socket SCJ | 110.2 | 3.8 | 67 |
| | 150mm x 6m | COMMSDUCT.150SN10.HDSA.6 | ● Salmon | HD | SN10 | Spigot/Socket SCJ | 160.3 | 5.3 | 28 |
| | 100mm x 6m | COMMSDUCT.100SN10.HDSAP.6 | ● Salmon Pink | HD | SN10 | Spigot/Socket SCJ | 110.2 | 3.8 | 67 |


ONE NZ BRANDED PVC-U RIGID COMMUNICATIONS DUCT

|  | Nominal Diameter (mm) | Order Code | Colour | Duty Classification | Stiffn ss Class | #Joint Type | Mean Outside Diameter (mm) | Wall Thickness (mm) | Pack Qty |
|---|-----------------------|-------------------------|--------------|---------------------|-----------------|-------------------|----------------------------|---------------------|----------|
| | 50 | ONE NZ 50C SOE | ● Light Blue | N/A | N/A | Spigot/Socket SCJ | 60.3 | 2.6 | 123 |
| | 100 | ONE NZ SN6.100.6 SOE | ● Light Blue | N/A | SN6 | Spigot/Socket SCJ | 110.2 | 3.2 | 67 |
| | 100 | ONE NZ SN10.100.6 SOE | ● Light Blue | N/A | SN10 | Spigot/Socket SCJ | 110.2 | 3.8 | 67 |
| | 50 | ONE NZ REPAIR SLEEVE 50 | ● Light Blue | N/A | N/A | Sleeve | 65.5 | 2.2 | 56 |

SECTION 6 RURAL SYSTEMS

IPLEX® PE FLEXIBLE COMMUNICATIONS DUCT


IPLEX® PE FLEXIBLE COMMUNICATIONS DUCT (SALMON)



| Nominal Diameter (mm) | Order Code | Colour | Coil Length | SDR Rating | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Maximum safe axial pulling load (KN) |
|-----------------------|---------------------------|----------|-------------|------------|----------------------------|--------------------------|--------------------------------------|
| 25mm | Cableduct SA 25/22.100 | ● Salmon | 100m | 17 | 25.1 | 1.7 | 1.0 |
| 32mm | Cableduct SA 32/25.500 | ● Salmon | 500m | 11 | 32.1 | 3.2 | 2.2 |
| 63mm | Cableduct SA 63/55.100 | ● Salmon | 100m | 17 | 63.3 | 4.0 | 5.8 |
| 110mm | Cableduct SA 110/97.100 | ● Salmon | 100m | 17 | 110.5 | 7.0 | 17.8 |
| 110mm | Cableduct SA 110/97.340** | ● Salmon | 340m | 17 | 110.5 | 7.0 | 17.8 |

** Supplied as a Drum Coil

IPLEX® PE FLEXIBLE COMMUNICATIONS DUCT (RED)



| Nominal Diameter (mm) | Order Code | Colour | Coil Length | SDR Rating | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Maximum safe axial pulling load (KN) |
|-----------------------|----------------------------|--------|-------------|------------|----------------------------|--------------------------|--------------------------------------|
| 25mm | COMMSDUCT Red 25/20.200 | ● Red | 200m | 11 | 25.1 | 2.5 | 1.3 |
| 25mm | COMMSDUCT Red 25/20.500 | ● Red | 500m | 11 | 25.1 | 2.5 | 1.3 |
| 32mm | COMMSDUCT Red 32/25.500 | ● Red | 500m | 11 | 32.1 | 3.2 | 2.2 |
| 32mm | COMMSDUCT Red 32/27.200 | ● Red | 200m | 13.6 | 32.1 | 2.6 | 1.8 |
| 50mm | COMMSDUCT Red 50/44.100 | ● Red | 100m | 17 | 50.2 | 3.2 | 3.7 |
| 63mm | Cableduct Red 63/55.100 | ● Red | 100m | 17 | 63.3 | 4.0 | 5.8 |
| 110mm | Cableduct Red 110/97.100 | ● Red | 100m | 17 | 110.5 | 7.0 | 17.8 |
| 110mm | Cableduct Red 110/97.340** | ● Red | 340m | 17 | 110.5 | 7.0 | 17.8 |

** Supplied as a Drum Coil

IPLEX® PE FLEXIBLE COMMUNICATIONS DUCT (COLOUR RAL 3015 - LIGHT PINK)













| Nominal Diameter (mm) | Order Code | Colour | Coil Length | SDR Rating | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Maximum safe axial pulling load (KN) |
|-----------------------|-------------------------|--------------|-------------|------------|----------------------------|--------------------------|--------------------------------------|
| 32mm | COMMSDUCT SAP 32/28.600 | ● Light Pink | 600m | 17 | 32.1 | 2.0 | 1.5 |
| 63mm | Cableduct SAP 63/55.100 | ● Light Pink | 100m | 17 | 63.3 | 4.0 | 5.8 |

SECTION 7






ENERGY & COMMUNICATIONS SYSTEMS

IPLEX® PE FLEXIBLE COMMUNICATIONS DUCT

CHORUS BRANDED PE FLEXIBLE COMMUNICATIONS DUCT

| | Size | Order Code | Colour | SDR Rating | Coil Length | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Maximum safe axial pulling load (KN) |
|---|------|-------------|----------------------------------|------------|-------------|----------------------------|--------------------------|--------------------------------------|
|  | 25mm | 20021788 | ● Green | 11 | 100 | 25.1 | 2.5 | 1.3 |
|  | 25mm | 20021789 | ● Green | 11 | 200 | 25.1 | 2.5 | 1.3 |
|  | 32mm | 10012829 | ● Black with red multistripes | 13.6 | 1000 | 32.1 | 2.6 | 1.8 |
|  | 32mm | 10012829500 | ● Black with red multistripes | 13.6 | 500 | 32.1 | 2.6 | 1.8 |
|  | 32mm | 10012830 | ● Black with green multistripes | 13.6 | 1000 | 32.1 | 2.6 | 1.8 |
|  | 32mm | 10012830500 | ● Black with green multistripes | 13.6 | 500 | 32.1 | 2.6 | 1.8 |
|  | 32mm | 10012831 | ● Black with violet multistripes | 13.6 | 1000 | 32.1 | 2.6 | 1.8 |
|  | 32mm | 10012831500 | ● Black with violet multistripes | 13.6 | 500 | 32.1 | 2.6 | 1.8 |
|  | 32mm | 10012832 | ● Black with brown multistripes | 13.6 | 1000 | 32.1 | 2.6 | 1.8 |
|  | 32mm | 10012832500 | ● Black with brown multistripes | 13.6 | 500 | 32.1 | 2.6 | 1.8 |


NON - CHORUS BRANDED PE FLEXIBLE COMMUNICATIONS DUCT

| | Nominal Diameter (mm) | Order Code | Colour | Coil Length | SDR Rating | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Maximum safe axial pulling load (KN) |
|---|-----------------------|--------------------------|---------------------------------|-------------|------------|----------------------------|--------------------------|--------------------------------------|
|  | 32mm | COMMSDUCT.32/27.1000RMS | ● Black with red multistripe | 1000m | 13.6 | 32.1 | 2.6 | 1.8 |
|  | 32mm | COMMSDUCT.32/27.1000GMS | ● Black with green multistripe | 1000m | 13.6 | 32.1 | 2.6 | 1.8 |
|  | 32mm | COMMSDUCT.32/27.1000LMS | ● Black with violet multistripe | 1000m | 13.6 | 32.1 | 2.6 | 1.8 |
|  | 32mm | COMMSDUCT.32/27.1000BRMS | ● Black with brown multistripe | 1000m | 13.6 | 32.1 | 2.6 | 1.8 |
|  | 110mm | Teleduct PE110/97.12CXGR | ● Green | 12m | 17 | 110.5 | 7.0 | 17.8 |

SECTION 6 RURAL SYSTEMS


IPLEX® PE FLEXIBLE COMMUNICATIONS DUCT

NON-CHORUS PE FLEXIBLE COMMUNICATIONS DUCT




| OD (mm) | Order Code | Colour | Coil Length | SDR Rating | Mean Outside Diameter (mm) | Mean Wall Thickness (mm) | Maximum safe axial pulling load (kN) |
|---------|-----------------------|--------------|-------------|------------|----------------------------|--------------------------|--------------------------------------|
| 32 | Teleduct PE32/25.100 | ● Lime Green | 100m | 11 | 32.1 | 3.2 | 2.2 |
| 32 | Teleduct PE32/25.200 | ● Lime Green | 200m | 11 | 32.1 | 3.2 | 2.2 |
| 32 | Teleduct PE32/25.500 | ● Lime Green | 500m | 11 | 32.1 | 3.2 | 2.2 |
| 32 | Teleduct PE32/27.200 | ● Lime Green | 200m | 13.6 | 32.1 | 2.6 | 1.8 |
| 32 | Teleduct PE32/27.500 | ● Lime Green | 500m | 13.6 | 32.1 | 2.6 | 1.8 |
| 32 | Teleduct PE32/28.200 | ● Lime Green | 200m | 17 | 32.1 | 2.0 | 1.5 |
| 32 | Teleduct PE32/28.500 | ● Lime Green | 500m | 17 | 32.1 | 2.0 | 1.5 |
| 40 | Teleduct PE40/35.200 | ● Lime Green | 200m | 17 | 40.1 | 2.6 | 2.3 |
| 50 | Teleduct PE50/44.100 | ● Lime Green | 100m | 17 | 50.2 | 3.2 | 3.7 |
| 63 | Teleduct PE63/55.50 | ● Lime Green | 50m | 17 | 63.3 | 4.0 | 5.8 |
| 63 | Teleduct PE63/55.100 | ● Lime Green | 100m | 17 | 63.3 | 4.0 | 5.8 |
| 63 | Teleduct PE63/55.150 | ● Lime Green | 150m | 17 | 63.3 | 4.0 | 5.8 |
| 110 | Teleduct PE110/97.50 | ● Lime Green | 50m | 17 | 110.5 | 7.0 | 17.8 |
| 110 | Teleduct PE110/97.100 | ● Lime Green | 100m | 17 | 110.5 | 7.0 | 17.8 |

SPARK BRANDED PE FLEXIBLE COMMUNICATIONS DUCT (COLOUR: PINK RAL4010)



| OD (mm) | Order Code | Colour | Coil Length | SDR Rating | Mean Outside Diameter (mm) | Mean Internal Diameter (mm) | Mean Wall Thickness (mm) | Maximum safe axial pulling load (kN) |
|---------|-------------------------|-----------|-------------|------------|----------------------------|-----------------------------|--------------------------|--------------------------------------|
| 110 | SPARK DUCT PE110/97.100 | ● Magenta | 100m | 17 | 110.5 | 96.5 | 7.0 | 17.8 |

ONE NZ BRANDED PE FLEXIBLE COMMUNICATIONS DUCT



| OD (mm) | Order Code | Colour | Coil Length | SDR Rating | Mean Outside Diameter (mm) | Mean Internal Diameter (mm) | Mean Wall Thickness (mm) | Maximum safe axial pulling load (kN) |
|---------|----------------------|-------------------------------------|-------------|------------|----------------------------|-----------------------------|--------------------------|--------------------------------------|
| 32 | ONE NZ PE 32/25.100 | ● Light Blue | 100m | 11 | 32.1 | 25.9 | 3.2 | 2.2 |
| 32 | ONE NZ PE 32/25.1000 | ● Light Blue | 1000m | 11 | 32.1 | 25.9 | 3.2 | 2.2 |
| 63 | ONE NZ PE 63/55.150 | ● Light Blue | 150m | 17 | 63.5 | 55.2 | 4.0 | 5.8 |
| 63 | ONE NZ PE 63/55.150B | ● Light Blue with black multistripe | 150m | 17 | 63.5 | 55.2 | 4.0 | 5.8 |
| 63 | ONE NZ PE 63/55.150R | ● Light Blue with red multistripe | 150m | 17 | 63.5 | 55.2 | 4.0 | 5.8 |
| 110 | ONE NZ 110/97.100 | ● Light Blue | 100m | 17 | 110.5 | 96.5 | 7.0 | 17.8 |








Drum coil

SECTION 7

ENERGY & COMMUNICATIONS SYSTEMS

IPLEX® PVC-U COMMUNICATIONS BENDS & FITTINGS

CHORUS BRANDED PVC-U COMMUNICATIONS BENDS

| | | Size | Order Code | Colour | Pack Qty |
|-----------------------|---|----------------------|------------|---------|----------|
| 20mm Formed Bend F&F |  | 20mm x 90° ROC* 240 | 10012582 | ● Green | 1 |
| | | 20mm x 90° ROC* 400 | 10013280 | ● Green | 1 |
| | | 20mm x 90° ROC* 530 | 10012939 | ● Green | 1 |
| | | 20mm x 90° ROC* 100 | 10013279 | ● White | 1 |
| | | 20mm x 90° ROC* 300 | 10012940 | ● White | 1 |
| 50mm Formed Bend M&F |  | 50mm x 30° ROC* 350 | 10013084 | ● Green | 1 |
| | | 50mm x 45° ROC* 200 | 10013087 | ● Green | 1 |
| | | 50mm x 45° ROC* 350 | 10013086 | ● Green | 1 |
| |  | 50mm x 45° ROC* 900 | 10013100 | ● Green | 1 |
| | | 50mm x 90° ROC* 350 | 10013088 | ● Green | 1 |
| | | 50mm x 90° ROC* 900 | 10013099 | ● Green | 1 |
| 100mm Formed Bend M&F |  | 100mm x 22° ROC* 900 | 10013098 | ● Green | 1 |
| | | 100mm x 30° ROC* 300 | 10013091 | ● Green | 1 |
| |  | 100mm x 45° ROC* 300 | 10013093 | ● Green | 1 |
| | | 100mm x 90° ROC* 350 | 10011337** | ● Green | 1 |
| |  | 100mm x 90° ROC* 400 | 10013095 | ● Green | 1 |
| | | 100mm x 90° ROC* 900 | 10013094 | ● Green | 1 |
| |  | 100mm x 90° ROC* 601 | 10013096 | ● Green | 1 |

*ROC = Radius of Curvature

CHORUS BRANDED PVC-U COMMUNICATIONS FITTINGS

| | Size | Order Code | Colour | Pack Qty |
|---|-------------|------------|---------|----------|
|  | 50mm | 10013109 | ● Green | 1 |
|  | 50mm x 20mm | 10012938 | ● Green | 1 |
|  | 50mm | P4004 | ● Black | 1 |
| | 100mm | P4005 | ● Black | 1 |

WHITE PVC-U COMMUNICATIONS BENDS

| | Size | Order Code | Colour | Pack Qty |
|---|----------|------------|---------|----------|
|  | 20 x 45° | CD8032045 | ● White | 1 |
|  | 20 x 90° | CD8032090 | ● White | 1 |


SECTION 6 RURAL SYSTEMS

FITTINGS FOR PE COMMUNICATIONS DUCTS

| | Order Code | Size (mm) | Ctn/Bag Qty |
|---|------------|-----------|-------------|
|  <p>Flexible Push-on Cap Removable Flexible Cap for Pipe End Protection</p> | 430.32 | 32 | 1 |
| | 430.40 | 40 | 1 |
| | 430.50 | 50 | 1 |
| | 430.63 | 63 | 1 |
| | 430.90 | 90 | 1 |
| | 430.110 | 110 | 1 |
| | 430.125 | 125 | 1 |
| | 430.140 | 140 | 1 |
| | 430.160 | 160 | 1 |
| | 430.180 | 180 | 1 |

IPLEX POLIGAS® PE GAS PIPE-METRIC DIMENSION

IPLEX POLIGAS® PE GAS PIPE - METRIC (OD) DIMENSION


| FREE STANDING COIL | Nominal Outside Diameter (mm) | Order Code | Coil Length | Outside Diameter (mm) | Colour | SDR |
|---|-------------------------------|-------------------|-------------|-----------------------|----------------------------------|-----|
|  | 25mm | 230.25SDR11.150 | 150m | 25.1 | ● Yellow | 11 |
| | 32mm | 230.32SDR11.150 | 150m | 32.1 | ● Yellow | 11 |
| | 63mm | 230.63SDR11.150 | 150m | 63.3 | ● Yellow | 11 |
| | 110mm** | 230.110SDR11.15BY | 15m | 110.5 | ● Black with Yellow Multistripes | 7 |
| STRAIGHT LENGTH | | | | | | |
|  | | | | | | |

Manufactured to AS/NZS 4130 Series 1

** Straight lengths

IPLEX POLIGAS® PE GAS PIPE-IMPERIAL (NOMINAL ID) DIMENSION

IPLEX® PE GAS PIPE - IMPERIAL (NOMINAL ID) DIMENSION


| FREE STANDING COIL | Nominal Internal Diameter (mm) | Order Code | Coil Length | Outside Diameter (mm) | Colour | SDR |
|---|--------------------------------|-----------------------|-------------|-----------------------|----------|-----|
|  | 10mm | 200.10.150.9 IMP | 150m | 15.7 - 16.0 | ● Yellow | 9 |
| | 15mm | 200.15.150.9 IMP SPL* | 150m | 21.4 - 21.7 | ● Yellow | 9 |
| | 20mm | 200.20.150.11 IMP | 150m | 26.6 - 26.9 | ● Yellow | 11 |
| | 25mm | 200.25.150.11 IMP | 150m | 33.4 - 33.7 | ● Yellow | 11 |
| | 32mm | 200.32.50.11 IMP | 50m | 88.7 - 89.2 | ● Yellow | 11 |
| | 32mm | 200.32.150.11 IMP | 150m | 42.1 - 42.4 | ● Yellow | 11 |
| | 50mm | 200.50.100.11 IMP | 100m | 60.2 - 60.5 | ● Yellow | 11 |
| | 80mm | 200.80.100.11 IMP | 100m | 88.7 - 89.2 | ● Yellow | 11 |
| | 100mm | 200.100.100.11 IMP | 100m | 114.1 - 114.7 | ● Yellow | 11 |

Manufactured to AS/NZS 4130 Series 3 (Nominal Internal Diameter Series)


*This SDR not included in AS/NZS4130, but is fully mechanically compliant with AS/NZS4130

SECTION 6 RURAL SYSTEMS

IPLEX POLIGAS® PE GAS PIPE

| DRUM COIL | Nominal Internal Diameter (mm) | Order Code | Coil Length | Outside Diameter (mm) | Colour | SDR |
|---|--------------------------------|--------------------|-------------|-----------------------|----------|-----|
|  | 100mm | 200.100.430.11 IMP | 430m | 114.1 - 114.7 | ● Yellow | 11 |

Drum Coils may be available in other sizes subject to minimum order quantity. Contact Iplex NZ for availability.

| STRAIGHT LENGTHS | Nominal Outside Diameter (mm) | Order Code | Length | Outside Diameter (mm) | Colour | SDR | Pack Qty |
|---|-------------------------------|--------------------|--------|-----------------------|----------|-----|----------|
|  | 32mm | 200.32.6.11 IMP* | 6m | 42.1 - 42.4 | ● Yellow | 11 | 5 |
| | 50mm | 200.50.6.11 IMP* | 6m | 60.2 - 60.5 | ● Yellow | 11 | 3 |
| | 80mm | 200.80.6.11 IMP* | 6m | 88.7 - 89.2 | ● Yellow | 11 | 1 |
| | 80mm | 200.80.12.11 IMP* | 12m | 88.7 - 89.2 | ● Yellow | 11 | 1 |
| | 100mm | 200.100.6.11 IMP* | 6m | 114.1 - 114.7 | ● Yellow | 11 | 1 |
| | 100mm | 200.100.12.11 IMP* | 12m | 114.1 - 114.7 | ● Yellow | 11 | 1 |
| | 150mm | 200.150.12.11 IMP* | 12m | 168.4 | ● Yellow | 11 | 1 |

* Manufactured to AS/NZS 4130 Series 3 (Nominal Internal Diameter Series)


Manufactured to AS/NZS 4130 Series 1

JOINTING ACCESSORIES

SECTION 8


JOINTING ACCESSORIES FOR PIPES

NOVAKEY® PVC SOLVENT CEMENT (PRESSURE APPLICATIONS)

| | Order Code | Size (ml) | No. in box |
|--|------------|-----------|------------|
|  | 9100.125P* | 125ml | 10 |
| | 9100.250P* | 250ml | 10 |
| | 9100.500P* | 500ml | 10 |
| | 9100.4P | 4 litres | 4 |
| *Contains internal brush Note: Iplex PVC Solvent Cement must always be used in conjunction with Iplex Cleaner Primer to achieve a good quality joint. | | | |


Solvent Cement (Blue)

NOVAKEY® PVC SOLVENT CEMENT (NON PRESSURE APPLICATIONS)

| | Order Code | Size (ml) | No. in box |
|--|-------------|-----------|------------|
|  | 9100.125NP* | 125ml | 10 |
| | 9100.250NP* | 250ml | 10 |
| | 9100.500NP* | 500ml | 10 |
| | 9100.4NP | 4 litres | 4 |
| *Contains internal brush Note: Iplex PVC Solvent Cement must always be used in conjunction with Iplex Cleaner Primer to achieve a good quality joint. | | | |

Solvent Cement (Clear)

NOVALUBE™ PIPE JOINTING LUBRICANT (NON-POTABLE WATER)


| | Order Code | Size (ml) | No. in box |
|---|------------|-----------|------------|
|  | 9136.500 | 500ml | 18 |
| | 9136.2 | 2 litres | 6 |
| | 9136.4 | 4 litres | 2 |
| Suitable for use on rubber ring joints in non-potable water pipelines, stormwater and sewer applications. | | | |

Pipe Lubricant


SECTION 8

JOINTING ACCESSORIES FOR PIPES


MEDLUBE™ PIPE JOINTING LUBRICANT (POTABLE WATER)

| | Order Code | Size (g) | Type | No. in box |
|---|--|----------|------|------------|
|  | 9137.275 | 275g | Tube | 38 |
| | 9137.500 | 500g | Pot | 12 |
| | 9137.2 | 2kg | Jug | 6 |
| | 9137.4 | 4kg | Jug | 4 |
| Medlube™ | Suitable for use on rubber ring joints in potable water pipelines and pressure applications. | | | |

NOVAKEY® CLEANER PRIMER (CLEAR)

| | Order Code | Size (ml) | No. in box |
|---|--|-----------|------------|
|  | 9101.250* | 250ml | 10 |
| | *Contains internal brush Note: Iplex Cleaner Primer must always be used in conjunction with Iplex Solvent Cement to achieve a good quality joint. | | |
| Cleaner Primer (Clear) | | | |

NOVAKEY® CLEANER PRIMER (PURPLE)

| | Order Code | Size (ml) | No. in box |
|---|--|-----------|------------|
|  | 9101C.500* | 500ml | 10 |
| | *Contains internal brush Note: The purple colour provides visual proof of use during the jointing process. Iplex Cleaner Primer must always be used in conjunction with Iplex Solvent Cement to achieve a good quality joint. | | |
| Cleaner Primer (Purple) | | | |

IPLEX® QUALITY MANAGEMENT SYSTEMS

Quality Assurance

Supplying products of consistently high quality is at the forefront of what we do at Iplex®, and central to our customer promise that Iplex® product quality meets or exceeds standards claimed.

All Iplex® manufacturing plants operate under a strict ISO 9001 Quality Management System (QMS). External certifying bodies carry out regular audits to provide third-party certification of the Company's QMS. Continued third-party product certification of Iplex® plastic pipeline products to relevant Australian & New Zealand standards, is also provided by these bodies.

The Iplex® laboratory is an IANZ accredited facility, providing added assurance that any measurement and testing is carried out professionally and in a technically reliable manner in accordance with international standards.



| APPLICABLE STANDARD | LICENCE TYPE | LICENCE NUMBER | CONFORMITY ASSESSMENT BODY |
|---------------------------------|--------------------|--------------------------------|-----------------------------|
| ISO 9001:2015 | QMS Accreditation | QEC4169 | SAI Global |
| ISO/IEC 17025:2017 | IANZ Accreditation | NUMBER 61 | IANZ |
| BEST ENVIRONMENTAL PRACTICE-PVC | BEP-PVC | SPROD40057 | SAI Global |
| AS/NZS 1254:2010 | StandardsMark™ | SMKP20126 & SMKP20180 | SAI Global |
| AS/NZS 1260:2017 | StandardsMark™ | SMKP20184, SMKP20185 & SMK1305 | SAI Global |
| AS/NZS 1260:2017 | WaterMark | WM 26953 | SAI Global |
| AS/NZS 1477:2017 | StandardsMark™ | SMK02569 & SMKP20181 | SAI Global |
| AS/NZS 1477:2017 | WaterMark | WM 26954 | SAI Global |
| AS/NZS 4130:2018 | StandardsMark™ | SMKP20400 | SAI Global |
| AS/NZS 4130:2018 | ISO Type 5 | AMI 74891 | Approval Mark International |
| AS/NZS 4441:2017 | StandardsMark™ | SMKP20682 | SAI Global |
| AS/NZS 4765:2017 | StandardsMark™ | SMK02570 | SAI Global |
| AS/NZS 61386.21:2015 | S-Mark | LIC 2901 & LIC 2910 | Bureau Veritas |

IPLEX® PIPELINES NZ THE COMPANY

Iplex® is one of New Zealand's leading manufacturers and suppliers of plastic pipeline systems. Iplex® provides products and services throughout New Zealand and to export markets around the Pacific and other international markets. Iplex® has manufacturing operations in Palmerston North, Christchurch and Ashburton, as well as access to the Iplex® Australian network.

Iplex® has been manufacturing plastic products since 1938 and in the early 1960's was a pioneer in the introduction of plastic pipeline systems into the New Zealand and Australian markets.

Iplex® services the following industry sectors:

Civil: Iplex® provides a wide range of solutions for wastewater, drainage and potable water pipeline projects. Manufacturing both PE (Polyethylene) & PVC (Polyvinylchloride) for both pressure and non-pressure (gravity fed) pipeline systems including civil infrastructure, drainage systems and roading systems.

Rural: Iplex® also service the rural market providing pipes and fittings for rural use. Iplex® provide systems for irrigation, stock water, land drainage, culverts and farm dairy effluent.

Plumbing: The Iplex® plumbing sector covers pipes and fittings used within the property boundary. This includes reticulation of potable and non-potable water, sanitary plumbing, wastewater, drainage and gas reticulation. Iplex® have the capabilities of supplying drain, waste and vent pipes and fittings, rainwater systems, traps and accessories.

Energy and Communications: An important sector for Iplex® NZ with a wide range of conduits, ducts and fittings available for new development and maintenance projects. The range covers electrical, communication and gas.



Iplex® Pipelines manufacturing plant and distribution hub in Palmerston North, New Zealand.

BUILDING CODE - DURABILITY

NEW ZEALAND BUILDING CODE - DURABILITY

The New Zealand Building Code places the responsibility on manufacturers to clearly state:

- a. the conditions for which products are or are not suitable;
- b. the durability and frequency of maintenance for the products' continued acceptable performance.

The Building Code categorises durability in the following way:

Clause B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- a. The life of the building, being not less than 50 years, if:
 - i. Those building elements (including floors, walls, and fixings) provide structural stability to the building, or
 - ii. Those building elements are difficult to access or replace, or
 - iii. Failure of those building elements to comply with the Building Code would go undetected during both normal use and maintenance of the building.
- b. 15 years if those building elements, including exposed plumbing in the subfloor space, are moderately difficult to access or replace
- c. 5 years if the building elements, including services, are easy to access and replace.

Iplex® Pipelines have adopted the following clauses for products such as the pipe and fittings that we manufacture.

Durability

The pipe or fitting will have a service life that is compatible with other pipe and fittings manufactured to the relevant AS/NZS Standard and any other recognised Standard if appropriate.

Thus correctly designed and installed drainage or pressure systems using Iplex® Pipelines' pipes or fittings will satisfy the performance requirements of both N.Z.B.C. Clause B2.3.1 (a) (50 years - services which are difficult to access or replace) and N.Z.B.C. Clause B2.3.1 (b) (15 years - services which are moderately difficult to access or replace).

Clauses (a) and (b) cover the majority of applications for products of our own manufacture, with the exception of rainwater pipes used above ground which satisfy the requirements of N.Z.B.C. Clause B 2.3 (c). (5 years - services which are easy to access and replace).

UNSUITABLE APPLICATIONS

1. Iplex® Pipelines PVC pressure pipes should not be used:

- i. As a conductor for earthing electrical appliances
- ii. With aromatic and chlorinated hydrocarbons, ketones, esters and ethers - refer to 'A guide to chemical resistance of thermoplastic and elastomeric materials' - available from Iplex® Pipelines
- iii. At continuous service temperature above 60°C (PVC-U) or 55°C (PVC-M) or 50°C (PVC-O)
- iv. Where provision for pressure derating has not been made above 25°C
- v. With any compressed air, or any gas applications
- vi. Without adequate support to the pipe both in above ground and below ground applications
- vii. Without adequate thrust support in above ground and below ground applications
- viii. Where depth of cover is less than:
 - 300mm where pipeline is not subject to vehicular loading
 - 450mm where pipeline is subject to vehicular loading not in roadways
 - 600mm where pipeline is subject to vehicular loading in sealed roadways
 - 750mm where pipeline is subject to vehicular loading in unsealed roadways
 - 750mm where pipeline is subject to construction equipment loading
- ix. Where working pressure + surge/cyclic pressure and dynamic pressure stresses exceed the nominated pressure/ performance rating, or exceed the dynamic stress (fatigue) performance capability of the pipe (POP -101)
- x. When exposed to direct sunlight for service applications, or storage exceeding 24 months from the date of manufacture, without protection. This protection in storage can include hessian or canvas covers to allow adequate cooling air circulation. Do not use plastic sheet or film covers which may heat and damage the pipe. Weathering protection in service can include physical shading such as under bridges or structures, or pale coloured U.V. resistant, water based, paint systems
- xi. With any service connection directly tapped into the pipe wall

2. Iplex® Pipelines polyethylene pressure pipes should not be used:

- i. As a conductor for earthing electrical appliances
- ii. All fire-rated applications
- iii. Transportation of automotive fuels
- iv. Transportation of drinking water in ground contaminated by automotive fuels, oils or synthetic hydrocarbons
- v. Coloured pipe or coloured stripe pipe (except black pipe) when exposed to direct sunlight for service applications, or storage exceeding 24 months from the date of manufacture, without protection. This protection in storage can include hessian or canvas covers to allow adequate cooling air circulation. Do not use plastic sheet or film covers which will heat and damage the pipes. Protection in service can include physical shading such as location under bridges or structures, or pale coloured U.V. resistant, water based, paint systems
- vi. Continuous service above 40°C internal or external temperature
- vii. Pressure pipes in continuous services up to 40° C internal or external temperature, where provision for pressure derating has not been made
- viii. Carrying chemicals outside the range advised by Iplex® Pipelines
- ix. Without adequate support to the pipe in above ground and below ground applications
- x. Where working pressure + surge/cyclic pressure and dynamic pressure stresses exceed the nominated pressure/ performance rating, or exceed the dynamic stress (fatigue) performance capability of the pipe (POP -010A) or fittings (POP -010B)
- xi. In below ground applications where depth of cover is less than:
 - 300mm where pipeline is not subject to vehicular loading
 - 450mm where pipeline is subject to vehicular loading not in roadways
 - 600mm where pipeline is subject to vehicular loading in sealed roadways
 - 750mm where pipeline is subject to vehicular loading in unsealed roadways
 - 750mm where pipeline is subject to construction equipment loading
- xii. In Slip Lining Applications using pressure grouting, where provision for internal structural support of the pipe by hydrostatic pressure has not been made
- xiii. In Horizontal Directional Drilling applications where the maximum safe axial tensile load for the pipe, advised by Iplex® Pipelines, has been exceeded

3. Iplex® Pipelines PVC Drain, Waste & Vent pipes, should not be used:

- i. With aromatic and chlorinated hydrocarbons, ketones, esters and ethers
- ii. For any pumped pressure applications
- iii. At continuous service temperatures above 60°C or for intermittent discharges of liquid above 75°C
- iv. Without adequate support to the pipe in either, above ground or, below ground applications
- v. In below ground applications (without added protection,) where depth of cover is less than:
 - 300mm where pipeline is not subject to vehicular loading
 - 450mm where pipeline is subject to vehicular loading not in roadways
 - 600mm where pipeline is subject to vehicular loading in sealed roadways
 - 750mm where pipeline is subject to vehicular loading in unsealed roadways
 - 750mm where pipeline is subject to construction equipment loading
- vi. when exposed to direct sunlight for service applications, or storage exceeding 24 months from the date of manufacture, without protection. In storage, this protection can include hessian or canvas covers to allow adequate cooling air circulation. Do not use plastic sheet or film covers which will heat and damage the pipes. Protection in service can include physical shading such as under bridges or structures, or pale coloured U.V. resistant, water based, paint systems

4. Iplex® PVC and PE Electrical Conduits and Ducts and PVC or PE Communication Ducts should not be used:

- i. For any pressure or gravity water applications
- ii. At continuous service temperatures above 60°C
- iii. Without adequate support to the pipe in either, above ground or, below ground applications
- iv. Conduits and Ducts coloured orange and all Communications Ducts when exposed without protection from direct sunlight for service applications, or storage exceeding 12 months from the date of manufacture. This protection in storage can include hessian or canvas covers to allow adequate cooling air circulation. Do not use plastic sheet or film covers which will heat and damage the pipes. Protection in service can include permanent physical shading such as location under bridges or structures, or by painting with pale coloured U.V. resistant, water based, paint systems

Note: *Unprotected coloured PVC ducts including orange, green, red, lilac and salmon will exhibit some colour fading (whitening) of directly exposed surfaces during medium term storage.*

Exposed Pole Riser Applications for Electrical and Communications ducts *Iplex Novadrain® DWV pipe to AS/NZS 1260 or Iplex Novakey® PVC-U pressure pipe PN 15 to AS/NZS 1477 can be used for permanently exposed protective ducts for Pole Riser applications without painting or shading.*

DEFINITION OF TERMS USED

| | | | |
|----------------|---|----------------|---|
| B | Black PE pipe with no external stripes or jacket | PE80 | MRS 8 polyethylene resin (formerly MDPE) to AS/NZS 4131 and conforming to PIPA POP 004 |
| BMS | Black PE pipe, with multiple blue external stripes | PE100 | MRS 10 polyethylene resin to AS/NZS 4131 and conforming to PIPA POP 004 |
| BSP | British standard pipe thread | PE100RC | RC raised crack resistant PE100, MRS 10 polyethylene resin conforming to AS/NZS 4131, and conforming to PIPA POP 016 and PIPA POP 004 |
| CMS | Black PE pipe with multiple cream external stripes | PN | Nominal maximum allowable working pressure (Bar) |
| CX | PE pipe with co-extruded coloured jacket on black inner | PVC-M | Modified polyvinylchloride |
| DN | Nominal diameter (mm) | PVC-O | Oriented polyvinylchloride |
| DWV | Drain waste and vent | PVC-U | Unplasticised polyvinylchloride |
| F&F | Female & Female (socket) | RRJ | Rubber ring joint |
| ID | Inside diameter | SCJ | Solvent cement joint |
| LDPE | Low density polyethylene | SDR | Standard dimension ratio = <u>Maximum mean outside diameter</u> Minimum wall thickness |
| HDPE | High density polyethylene | SN | Nominal minimum pipe ring bending stiffness class as defined in AS/NZS 1260 (KN/m ²) and AS/NZS 61386.21 |
| LMS | Black PE pipe with multiple lilac external stripes | SOE | Socketed one end (for solvent cement jointing) |
| M&F | Male (spigot) & Female (socket) | | |
| OD | Nominal outside diameter | | |
| PE | Polyethylene | | |

MAXIMUM ALLOWABLE WORKING PRESSURE CONVERSION TABLE

| PN | BAR | METRES HEAD | PVC PIPE MATERIAL | KPA | P.S.I | FORMER PRESSURE CLASS |
|------|------|-------------|---------------------|------|-------|-----------------------|
| 6 | 6 | 60 | PVC-U, & PVC-M | 600 | 87 | B |
| 6.3 | 6.3 | 63 | PVC-O | 630 | 91 | |
| 9 | 9 | 90 | PVC-U & PVC-M | 900 | 130 | C |
| 10 | 10 | 100 | PVC-O | 1000 | 145 | |
| 12 | 12 | 120 | PVC-U & PVC-M | 1200 | 174 | D |
| 12.5 | 12.5 | 125 | PVC-O | 1250 | 181 | |
| 15 | 15 | 150 | PVC-U & PVC-M | 1500 | 217 | E |
| 16 | 16 | 160 | PVC-O & PVC-M | 1600 | 232 | |
| 18 | 18 | 180 | - | 1800 | 261 | F |
| 20 | 20 | 200 | - | 2000 | 290 | G |
| | | | PE PIPE MATERIAL | | | |
| 5 | 5 | 50 | LDPE | 500 | 72 | |
| 6.3 | 6.3 | 63 | PE100/PE100RC | 630 | 91 | |
| 7 | 7 | 70 | LDPE | 700 | 101 | |
| 8 | 8 | 80 | LDPE, PE100/PE100RC | 800 | 116 | |
| 9 | 9 | 90 | LDPE, PE100/PE100RC | 900 | 130 | |
| 10 | 10 | 100 | PE100/PE100RC | 1000 | 145 | |
| 12.5 | 12.5 | 125 | PE80, PE100/PE100RC | 1250 | 181 | |
| 16 | 16 | 160 | PE100/PE100RC | 1600 | 232 | |
| 20 | 20 | 200 | PE100/PE100RC | 2000 | 290 | |
| 25 | 25 | 250 | PE100/PE100RC | 2500 | 362 | |

PRODUCT CATALOGUE, MAY 2026

LIMITATIONS

The information contained in this document is current as of May 2026 and is based on data available to Iplex® Pipelines NZ Ltd at the time of going to print.

All photographic images are intended to provide a general impression only, and should not be relied upon as an accurate example of Iplex® Pipelines NZ Ltd products, installed in accordance with this document or the referenced compliance documents.

This publication replaces all previous editions of the Iplex® Pipelines Product Catalogue. Iplex® Pipelines NZ Ltd reserves the right to change the information contained in this document without prior notice. It is your responsibility to ensure that you have the most up to date information available. You can call toll free on 0800 800 262 or visit www.iplex.co.nz to obtain current information.

Iplex® Pipelines NZ Ltd has used all reasonable endeavours to ensure the accuracy and reliability of the information contained in this document. However, to the maximum extent permitted by law, Iplex® Pipelines NZ Ltd assumes no responsibility or liability for any inaccuracies, omissions or errors in this information nor for any actions taken in reliance on this information. Pipes and fittings have been shown as typical configurations, however, in some cases product dimensions may vary or be changed without notice. In all instances, the reader should contact Iplex® Pipelines for clarification that the specific product is appropriate for their circumstance.

TRADEMARKS

The names Iplex®, Apollo®, Volta®, Aquacell®, Blackline™, Blackline HP™, Rural Black™, Blueline®, Farmtuff®, Farmtrac®, Greenline®, Nexus®, Nexusflo™, Nexuscoil™, Novaflo®, Novacoil®, Novadrain®, Novakey®, Poligas®, Poliplex®, Redline®, Restrain®, Rhino®, Alkathene™, Farmline™, Stormfit® and Superstorm® are registered or active trade marks of Fletcher Building Holdings Limited.

COPYRIGHT

© Copyright 2026, Iplex® Pipelines NZ Ltd. All of the material contained in this Product Catalogue, including all text, tables, charts, graphs, drawings, images and diagrams, are protected by copyright. These materials may not be reproduced, adapted or transmitted in any form by any process, without the permission of Iplex® Pipelines NZ Ltd.



IPLX PIPELINES NZ LIMITED

0800 800 262

AUCKLAND: 810 GREAT SOUTH ROAD, PENROSE

PALMERSTON NORTH: PRIVATE BAG 11019, 67 MALDEN STREET

CHRISTCHURCH: PO BOX 16225, 22 BRAEBURN DRIVE, SOCKBURN

ASHBURTON: 13 ASHFORD AVENUE, NEWLANDS

www.iplex.co.nz