




Code Explanation	
Product Code	Coil length (metres)
NEXUS110.100	
OD (mm)	



Iplex Nexusflo, slotted with **BLUE** Stripe



Code Explanation	
Product Code	Coil length (metres)
NEXUSCOIL110.100	
OD (mm)	





Iplex Nexuscoil, unslotted with **Yellow** Stripe

Iplex NEXUS® is a twin wall HDPE pipe combining a smooth inner wall with a corrugated outer wall. During manufacture, the two walls are welded together, providing structural stiffness with smooth bore flow performance. Iplex NEXUSFLO is slotted whilst Iplex NEXUSCOIL is unslotted. NEXUS® pipe is available in standard OD sizes 110mm, 160mm and 200mm.

Features & Benefits of Iplex Nexusflo and Iplex Nexuscoil

Smooth Bore	NEXUS smooth bore supports flow performance , and installation at lower gradients, compared with a similar size Iplex Novaflo corrugated bore alternative
Coupling	All sizes of Nexus are provided with a factory fitted, end load resistant coupler on each coil
Twinwall	NEXUS corrugated outer wall, and twinwall construction, gives underground structural performance
Flexible	NEXUS pipe flexibility assists with pipe handling and location during installation
Fittings	NEXUS is compatible with commercially available injection moulded PVC DWV and Stormwater, fittings to assist with flexibility of use.
Sizes	NEXUS is available in three diameters allowing a degree of choice to match the performance requirement.
Material	NEXUS is manufactured from high density polyethylene (HDPE) , a plastic material which is impact resistant, rust proof, abrasion resistant, and durable for in-ground service.
Quality System	NEXUS is manufactured in New Zealand by Iplex Pipelines using a Quality Management System accredited to AS/NZS ISO 9001:2015
Identification	NEXUSFLO and NEXUSCOIL are colour coded with a co-extruded coloured stripe to aid product identification
Recycled HDPE	NEXUS contains significant proportions of Post Consumer Recycled HPDE material derived from local sources within New Zealand

Product Diameters and Coil lengths




	Diameter OD (mm)	Length or Coil Size (metres)	Colour of pipe & stripe
Iplex NEXUSFLO (slotted)	110	15, 30, 50, 100, 450	Black with blue stripe 
	160	45, 185	
	200	5, 29, 120	
Iplex NEXUSCOIL (Unslotted)	110	15, 30, 50, 100, 450	Black with yellow stripe 
	160	45, 185	
	200	29, 120	

Product Range

Product	Product Code	Nominal OD (mm)	Length of coils (m)	Colour
NEXUSFLO (punched)	NEXUS11015	110	15	● Black w/ Blue Stripe
	NEXUS11030	110	30	● Black w/ Blue Stripe
	NEXUS11050	110	50	● Black w/ Blue Stripe
	NEXUS110100	110	100	● Black w/ Blue Stripe
	NEXUS110450	110	450	● Black w/ Blue Stripe
	NEXUS16045	160	45	● Black w/ Blue Stripe
	NEXUS160185	160	185	● Black w/ Blue Stripe
	NEXUS2005	200	5	● Black w/ Blue Stripe
	NEXUS20029	200	29	● Black w/ Blue Stripe
	NEXUS200120	200	120	● Black w/ Blue Stripe
NEXUSCOIL (unpunched)	NEXUSCOIL11015	110	15	● Black w/ Yellow Stripe
	NEXUSCOIL11030	110	30	● Black w/ Yellow Stripe
	NEXUSCOIL11050	110	50	● Black w/ Yellow Stripe
	NEXUSCOIL110100	110	100	● Black w/ Yellow Stripe
	NEXUSCOIL110450	110	450	● Black w/ Yellow Stripe
	NEXUSCOIL16045	160	45	● Black w/ Yellow Stripe
	NEXUSCOIL160185	160	185	● Black w/ Yellow Stripe
	NEXUSCOIL20029	200	29	● Black w/ Yellow Stripe
	NEXUSCOIL200120	200	120	● Black w/ Yellow Stripe

Fittings for Iplex NEXUSFLO™ & Iplex NEXUSCOIL™

PVC and PE moulded fittings for use with the IPLEX NEXUSFLO™ and Iplex NEXUSCOIL™ range of pipes.

Reducing Junction F&F		Plain Junction F&F		Level Invert F&F	
					
Size (mm)	Product Code	Size (mm)	Product Code	Size (mm)	Product Code
160 x 110 x 45	704.160.110.45	65 x 45	104.65.45	160 x 110	123.150.110S
		110 x 45	104.100.45	(Socketed both ends)	
		160 x 45	104.150.45		

Coupler F&F		Coupler F&F		End Cap	
					
Size (mm)	Product Code	Size (mm)	Product Code	Size (mm)	Product Code
65	410.065	110	420.110	110	430.110
		160	420.160	160	430.160
		200	420.200		

iplex.co.nz

Iplex Pipelines NZ Limited

Call 0800 800 262 or Fax

0800 800 804